

“MP” Concrete Agitator

JS500, JS750 and JS1000 concrete mixers are used for many kinds of prefabricated-component factories water conservancy, roads, bridges and other industrial, civil construction projects to mixing dry concrete, fluidity concrete lightweight aggregate concrete and various mortars. They can work independently and also with corresponding batching machine together as mixing plant. They have many characteristics, such as reasonable structure, good mixing quality, high efficiency, low energy consumption, small noise and so on. The scaleboards and mixing blades are used high hardness, high tenacity and wear-resistant alloy steel casting, and have high performance and high reliability.



1

Technical Data

Parameter		Model		
		MPJS500	MPJS750	MPJS1000
Expected capacity		500L	750L	1000L
Feed capacity		800L	1200L	1600L
Productivity		more than 25 m ³ /h	more than 35 m ³ /h	more than 40 m ³ /h
Discharge height		1500mm	1600mm	2700mm/3800mm
Hopper upgrade speed		18m/min	18m/min	21.9m/min
Mixing motor	power	18.5kw	30 kw	37 kw
	model	YEZ1325-4-B5	YEZ132M-4-B5	YEZ160S-4
Hoist motor	power	4.5-5.5 kw	7.5 kw	11 kw
	model	50DWB20-8A	65DWB35-5	KQW65-1001
Pump motor	power	750w	1.1kw	3kw
Max aggregate size		60-80mm	60-80mm	60-80mm
Dimension		2850x2700x5246mm	5138x4814x6388mm	5338x3300x6510mm
Total weight		4200kg	7156kg	8000kg

For further information, please feel free to contact Mr Johnson Kwan.on 9236 3957