



## MPU29

Reversible Vibratory Plates



### German design reversible vibration plate.

This very robust Wacker Neuson reversible plate offers functionality and performance at a value price. The compact design allows for compaction of mixed soils, trenches, landscaping and maintenance.

- The auto-lock guide handle can be locked into a vertical position for easy transport and storage and forward / Reverse control located on handle for safe and easy access.
- Heavy-duty protective frame features a central lifting point for easy on / off loading and placement of plate into trenches.
- Tough ductile iron baseplate is extremely durable even under extreme conditions and provides for long service life.
- As additional safety feature, the machine will automatically return to spot compaction when handle is released and
- Eye bracket in front of machine for easy transport in the field using rope or hook and lift eye for easy on / off loading of the plate.

**MPU29 Standard Package includes operator's manual and parts book.**

MPU29 Item No. 0630141



## Technical specifications

### Operating data

|   |              |
|---|--------------|
| Operating weight (without water / fuel) | 167 kg       |
| Centrifugal force                       | 29 kN        |
| Base plate size (w × l)                 | 500 × 700 mm |
| Frequency                               | 90 Hz        |
| Advance travel (forward)                | 13.04 m/min  |
| Gradeability                            | 35 %         |
| Transport height                        | 1,353 mm     |
| Transport length                        | 750 mm       |
| Transport width                         | 575 mm       |
| Shipping weight (including packaging)   | 178 kg       |

### Engine / Motor

|                             |   |
|-----------------------------|---|
| Engine / Motor type         | Gasoline engine, air cooled, 4 stroke, OHV, single cylinder |
| Engine / Motor manufacturer | Wacker Neuson   |
| Engine / Motor              | WN9   |
| Displacement                | 270 cm <sup>3</sup>   |
| Engine performance (max.)   | 6.6 kW  |
| at rpm (full throttle)      | 3,600 rpm   |
| Fuel consumption            | 1.52 l/h  |
| Tank capacity (fuel)        | 6.5 l   |

**Please note**

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions.

Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2015 Wacker Neuson SE.