



MFS12



Outstanding performance and excellent value

These compact and lightweight floor saws offer outstanding cutting performance, smooth operation and excellent maneuverability. These units bridge the gap between a hand-held cutoff saw and a larger walk-behind floor saw, and are ideal for small cuts in asphalt and concrete, for patching and repairs jobs and applications such as installing electric fencing, lighting, etc. Due to their compact size they will fit in every truck and won't take away much space in any warehouse.

- Weight of the engine above the cutting shaft keeps the blade down during cutting, and provides for a stable and non-wavy cut - no need for pushing the machine down! This not only provides for a truly outstanding cutting performance in their class, it even increases blade life too.
- One-touch blade guard can be easily opened any time without any tools, for quick and convenient blade changing.
- Operating handle can be easily adjusted without tools to operator's body height, provides high user comfort.
- Durable water tank can quickly be removed without tools for refill or storage.
- Additional features like the parking brake and lifting hook make MFS12 have the most excellent value.



Technical specifications

L x W x H (handle not extended)	856 x 422 x 769 mm
Weight (without water/fuel)	53 kg
Blade diameter	305 mm
Blade arbor	27 mm
Cutting depth (max.)	110 mm
Nominal speed	3,300 rpm
Tank capacity (water)	14.2 l
Engine / Motor	Air-cooled, single cylinder, 4-cycle gasoline engine
Engine / Motor manufacturer	Wacker Neuson
Engine / Motor type	N7
Displacement	212 cm ³
Power (max.)	4.2 kW
Power	5.7 kW (hp)
at rpm	3,600 rpm
Fuel type	Gasoline
Fuel consumption	1.17 l/h
Tank capacity (fuel)	3.6 l
Starting device	Recoil

Please note

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions.

Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2015 Wacker Neuson SE.