



MS64A

4 Stroke Rammer



Four-cycle rammers deliver outstanding performance

Add a Honda GX100 4-cycle engine to the preferred vibratory rammer design in the industry and you have a winning combination. These 4-cycle vibratory rammers are designed for the compaction of cohesive, mixed and granular soils in confined areas.

- Dedicated 4-cycle crankcase for increased durability and simplified maintenance.
- Float bowl carburetor for easy service.
- Long durable recoil rope for tough rammer application.
- Steel engine guards for maximum protection.



Technical specifications

Operating data

Operating weight	71 kg
Ramming shoe size (WxL)	280 × 342 mm
L x W x H	990 × 380 × 690 mm
Stroke	46 mm
Percussion rate	615 blows/min
Operating speed (travel)	7.8 m/min

Engine / Motor

Engine / Motor type	air-cooled, 4-cycle, single cylinder, Honda GX 100 gasoline engine
Engine / Motor manufacturer	Honda
Engine / Motor	GX 100
Displacement	98 cm ³
Operating performance (SAE J1995)	2.4 kW
at rpm	4,400 rpm
Fuel consumption	0.9 l/h
Tank capacity	3 l

Please note

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions.

Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2015 Wacker Neuson SE.