



KD 4x4
Coldwater HighPressure Cleaner

- ▶ Mobile coldwater Unit for professional use
- ▶ Impact resistant rotation-moulded Chassis and Cover for long durability
- ▶ Triplex-Piston Pump with Brass Pump-Head, Ceramic-Plungers and st.st. Valves
- ▶ Multi-Functional Storage Facility for HP-Hose, electr. Cable and chemical intake Hose.
- ▶ Multi-Storage Facility for Trigger-Gun, Spray-Wand and Rotary-Nozzle integrated in Chassis
- ▶ Water Break-Tank with 35 l capacity
- ▶ High-Pressure Chemical with Regulator-Valve
- ▶ Infinitely variable pressure control
- ▶ 2-fold safety system with overload protection
- ▶ **Standard equipment** TSS-System: Total Start-Stop System with Off-Delay, Unit Total-Switch Off after 20 min, Leakage Recognition, Professional Hose-Reel with st.st. Shaft and 20m Hose, Watertank with 35l capacity, High-Pressure Detergent with Regulator-Valve, Rotary-Nozzle, High-Pressure Nozzle c/w. stainless steel Lance and Nozzle-Protection



*Units show Options

Technical data	Unit	KD 1140	KD 1340	KD 1840/ 140 bar	KD 1540	KD 1840/ 180 bar
Pressure	bar/ Mpa	30-250/ 3-25	30-180/ 3-18	30-140/ 3-14	30-280/ 3-28	30-180/ 3-18
Waterflow	l/min	16	21	30	25	30
Connected load	kW	7,9	7,9	7,9	14,0	14,0
Voltage	Ph/V/Hz	3/400/50	3/400/50	3/400/50	3/400/50	3/400/50
Temperature	C°	40	40	40	40	40
Nozzle size		2504 	2506 	2512 	2507 	2510
HighPressure hose	m/NW [mm]	20/8	20/8	20/10	20/8	20/10
Engine speed	rpm	1400	1400	1400	1400	1400
Weight	kg	98	98	101	125	125
Part No.		551	552	563	553	554