



HDE

**Hotwater HighPressure Cleaner,
electric-heated**

- ▶ Mobile hotwater Unit for professional use
- ▶ Metal-Chassis corrosion protected (fully zinc coated, iron phosphatied, Powder coated) with impact resistant unit cover
- ▶ Security system consisting of pressure switch, unloader valve, safety valve, thermostat and overload protection
- ▶ Transparent Containers for visual level control
- ▶ Electrically heated - Emission free!
- ▶ Large stainless steel Boiler for hotwater storage with 12, 18 or 24 kW Heating power
- ▶ Over heat protection in boiler
- ▶ Detergent Valve for precise metering of cleaning fluids
- ▶ Infinitely variable pressure and temperature control
- ▶ Stand-By System for immediate operation
- ▶ TSS-System with Pump Off-Delay
- ▶ Hotwater resistant High-Pressure Pump
- ▶ 2 x 20 l Detergent Container
- ▶ Option: Hose Reel up to max. 40 m HP-Hose possible
- ▶ **Standard equipment:** 10m H.P.Hose, Trigger-Gun Power 315 ST, stainless steel Lance 900mm, Nozzle-Protection and stainless steel High-Pressure Nozzle and Nozzle Protection



Technical data	Unit	HDE 800-12 kW	HDE 800-18 kW	HDE 800-24 kW
Pressure	bar/ Mpa	30-160/ 3-16	30-160/ 3-16	30-160/ 3-16
Waterflow	l/min	11	11	11
Connected load	kW	16,0	22,0	28,0
Voltage	Ph/V/Hz	3/400/50	3/400/50	3/400/50
Temperature	C°	30-80	30-80	30-80
Nozzle size		2504 <input type="checkbox"/>	2504 <input type="checkbox"/>	2504 <input type="checkbox"/>
HighPressure hose	m/NW [mm]	10/8	10/8	10/8
Engine speed	rpm	1400	1400	1400
Weight	kg	145	150	155
Part No.		106	107	108