

明力油壓機械工程 Main Power Hydraulics Machinery Co. Tel: 852 - 2690 3509 Fax: 852 - 2690 3505 Website: http://www.mainpowerhyd.com/ E-mail: maingphk@netvigator.com

"BETONOL 100"

Concrete dissolving agent with corrosion protection effect

Properties	Special liquid product with	
	an acid reaction and a	
	brownish, clear, transparent	
	appearance. The product has	
	a specifically sour scent. The	
	well matched composition of	
	agents ensures the optimum	
	removal of wet concrete and	
	concrete that set for some	
	time and largely protects	
	materials against corrosion.	



Application	The product is designed for cleaning concrete trucks, concrete mixers, concrete guns,		
	concrete containers, etc.		
Dosage	Apply undiluted on the soiled surfaces by scrubbing or brushing. Allow to react and		
	rinse off with hard water jet. If necessary, repeat treatment.		
Specifications	pH value conc. potentiometric	0.2	
	pH value 1:50 potentiometric	1.1	
	Density at 20 °C/68 °F	1.08 kg/l	
Ingredients	Inhibitors, hydrochloric acid, auxiliary agents		
Safety	The product reacts corrosive and irritates the respiratory system.		
Precautions	Keep out of the reach of children! If the product gets in contact with the eyes, wash		
	with plenty of water and seek medical attention. Please observe your local		
	governmental safety regulations.		
Remarks	Removes concrete that has set for max. 6 - 8 hours.		

The materials contained herein are based on our experience, intended for general information only, and subject to change. As working conditions are beyond our control and due to the wide range of application, operation and quality of materials to be cleaned, we do not take any responsibility or liability as regards the results. Please observe your local governmental regulations.