



Art. no. **9410**

Automatic rewind, spring-driven hose reel, **series "Easy Steel"**, in painted steel, with enclosure in painted steel and polyurethane hose 8 x 12 mm and 10 m length, suitable for the use with compressed air and water at low pressure.

Art. no. **9413**

Automatic rewind, spring-driven hose reel, **series "Easy Steel"**, in painted steel, with enclosure in painted steel and polyurethane hose 10 x 14 mm and 10 m length, suitable for the use with compressed air and water at low pressure.



Pivoting wall mounting bracket

Art. no.	Hose length	Hose ø	Connection threads IN - OUT	Max working pressure	Weight	Dimensions (LxWxH) (mm)
9410	10 m	8x12 mm	1/4" BSP (F) - 1/4" BSP (M)	15 bar	11 kg	220x310x380
9413	10 m	10x14 mm	1/4" BSP (F) - 1/4" BSP (M)	15 bar	11 kg	220x310x380



Art. no. **9510**

Automatic rewind, spring-driven hose reel, **series "Easy Steel"**, in stainless steel AISI 304, with enclosure in stainless steel and polyurethane hose 8 x 12 mm and 10 m length, suitable for the use with compressed air and water at low pressure.

Art. no. **9511**

Automatic rewind, spring-driven hose reel, **series "Easy Steel"**, in stainless steel AISI 304, with enclosure in stainless steel and polyurethane hose 10 x 14 mm and 10 m length, suitable for the use with compressed air and water at low pressure.

Art. no.	Hose length	Hose ø	Connection threads IN - OUT	Max working pressure	Weight	Dimensions (LxWxH) (mm)
9510	10 m	8x12 mm	1/4" BSP (F) - 1/4" BSP (M)	15 bar	11 kg	220x310x380
9511	10 m	10x14 mm	1/4" BSP (F) - 1/4" BSP (M)	15 bar	11 kg	220x310x380

