



Art. no. 9210

Automatic rewind, spring-driven hose reel, in painted steel, provided for exhaust extraction, with crush proof hose in different diameters and lengths, hose stop bumper and beak nozzle with diaphragm lid.

Art. no.	Suitable for hose diameter	Max hose length
9210/7510	Ø 75 mm	10 m
9210/7515	Ø 75 mm	15 m
9210/10010	Ø 100 mm	10 m
9210/10015	Ø 100 mm	15 m
9210/12510	Ø 125 mm	10 m
9210/12515	Ø 125 mm	15 m
9210/15010	Ø 150 mm	10 m



Art. no. 9212

Automatic rewind, spring-driven hose reel, in painted steel, provided for exhaust extraction, with electric centrifugal fan, crush proof hose in different diameters and lengths, hose stop bumper and beak nozzle with diaphragm lid.

Art. no.	Suitable for hose diameter	Max hose length	Power	Voltage
9212/6010	Ø 60 mm	10 m	0,37 kW	380 VAC / 50 Hz
9212/7510	Ø 75 mm	10 m	0,75 kW	380 VAC / 50 Hz
9212/7515	Ø 75 mm	15 m	0,75 kW	380 VAC / 50 Hz
9212/10010	Ø 100 mm	10 m	0,75 kW	380 VAC / 50 Hz
9212/10015	Ø 100 mm	15 m	0,75 kW	380 VAC / 50 Hz
9212/12510	Ø 125 mm	10 m	0,75 kW	380 VAC / 50 Hz
9212/12515	Ø 125 mm	15 m	0,75 kW	380 VAC / 50 Hz
9212/15010	Ø 150 mm	10 m	1,1 kW	380 VAC / 50 Hz



Art. no. 9214

Miniset with electric centrifugal fan, double crush proof hose in different diameters and lengths, hose stop bumper and beak nozzle with diaphragm lid, provided for exhaust extraction, suitable for the use in 1 or 2 posts.

Art. no.	Suitable for hose diameter	Max hose length	Power	Voltage
9214/7510	Ø 75 mm	10 m	0,75 kW	380 VAC / 50 Hz
9214/7515	Ø 75 mm	15 m	0,75 kW	380 VAC / 50 Hz
9214/10010	Ø 100 mm	10 m	0,75 kW	380 VAC / 50 Hz
9214/10015	Ø 100 mm	15 m	0,75 kW	380 VAC / 50 Hz
9214/12510	Ø 125 mm	10 m	0,75 kW	380 VAC / 50 Hz
9214/12515	Ø 125 mm	15 m	0,75 kW	380 VAC / 50 Hz
9214/15010	Ø 150 mm	10 m	1,1 kW	380 VAC / 50 Hz



Art. no. 9216 - Art. no. 9218

Wall mounted suction system for exhaust extraction for single or two work stations. It's inclusive of a fan with backward blade fan wheel, crush-proof hose in different diameters and lengths, hose stop bumper and beak nozzle with diaphragm lid.

Art. no.	Suitable for hose diameter	Max hose length	Power	Voltage
9216/75075	Ø 75 mm	7,5 m	0,75 kW	380 VAC / 50 Hz
9216/7510	Ø 75 mm	10 m	0,75 kW	380 VAC / 50 Hz
9216/100075	Ø 100 mm	7,5 m	0,75 kW	380 VAC / 50 Hz
9216/10010	Ø 100 mm	10 m	0,75 kW	380 VAC / 50 Hz
9218/75075	Ø 75 mm	7,5 m	1,1 kW	380 VAC / 50 Hz
9218/7510	Ø 75 mm	10 m	1,1 kW	380 VAC / 50 Hz
9218/100075	Ø 100 mm	7,5 m	1,1 kW	380 VAC / 50 Hz
9218/10010	Ø 100 mm	10 m	1,1 kW	380 VAC / 50 Hz