



Art. no. **9270**

Automatic rewind, spring-driven hose reel, in painted steel, provided for the installation of max 10 m – twin hose in 1/2", with hose inlet connection fittings, suitable to connect welding equipment.

The hose reel is supplied without hoses and can be used with twin hoses (blue - red) for welding gases oxygen and acetylene in SBR/EPDM according to norm EN 559:1994.

On demand also available in stainless steel AISI 304.

Art. no.	Hose reel material	Max working pressure	Connection threads IN - OUT	Max length hose	Max operating temperature	Weight	Dimensions (LxWxH) (mm)
<b>9270</b>	Painted steel	200 bar	1/2" BSP (M) – 1/2" BSP (F)	10 m	90°C	18 kg	280x610x640



Art. no. **9418**

Automatic rewind, spring-driven hose reel, in painted steel, with 20 m – twin hose (blue - red) in 5/16" - 2 x 8 mm for welding gases oxygen and acetylene (in SBR/EPDM according to norm EN 559:1994 max 20 bar - 90°C), hose inlet connection fittings, shaft and swivel joint in brass; suitable to connect welding equipment.

On demand also available in stainless steel AISI 304.



Art. no.	Hose reel material	Max working pressure	Connection threads IN - OUT	Max length hose	Max operating temperature	Weight	Dimensions (LxWxH) (mm)
<b>9418</b>	Painted steel	20 bar	3/8" BSP (F) – 3/8" BSP (F)	20 m	150 mm	32 kg	280x610x640