



Art. no. **9527/EX+289408**

Art. no. **9527/EX+289408**

Automatic rewind, spring-driven hose reel, adjustable arms series, in stainless steel AISI 304, in accordance with directive ATEX 94/9/EC – group II – category 2, with 8 m - rubber hose 1" (ø int. 25 mm), suitable for the supply of petrol in accordance with norm EN 1761:1994.



Art. no.	Max pressure	Connection threads inlet - outlet	Internal ø inlet swivel joint	ø / Length delivery hose	Width reel	Weight	Dimensions (LxWxH) (mm)
<b>9527/EX+289408</b>	18 bar	1" BSP (M) – 1" BSP (F)	20 mm	1" – 8 m	150 mm	29 kg	290x460x450

Optional



Art. no. **9765**

Swivel bracket



Art. no. **9525/EX+289415**

Art. no. **9525/EX+289415**

Automatic rewind, spring-driven hose reel, heavy duty series, in stainless steel AISI 304, in accordance with directive ATEX 94/9/EC – group II – category 2, with 15 m - rubber hose 1" (ø int. 25 mm), suitable for the supply of petrol in accordance with norm EN 1761:1994.




Art. no.	Max pressure	Connection threads inlet - outlet	Internal ø inlet swivel joint	ø / Length delivery hose	Width reel	Weight	Dimensions (LxWxH) (mm)
<b>9525/EX+289415</b>	18 bar	1" BSP (M) – 1" BSP (F)	20 mm	1" – 15 m	300 mm	38 kg	460x590x450

Optional



Art. no. **9764**

Swivel bracket



Art. no. **9536/EX+289425**

Art. no. **9536/EX+289425**

Automatic rewind, spring-driven hose reel, adjustable arms series, in stainless steel AISI 304, in accordance with directive ATEX 94/9/EC – group II – category 2, with 25 m - rubber hose 1" (ø int. 25 mm), suitable for the supply of petrol in accordance with norm EN 1761:1994.



Art. no.	Max pressure	Connection threads inlet - outlet	Internal ø inlet swivel joint	ø / Length delivery hose	Width reel	Weight	Dimensions (LxWxH) (mm)
<b>9536/EX+289425</b>	18 bar	1" BSP (M) – 1" BSP (F)	20 mm	1" – 25 m	400 mm	61 kg	520x550x540

