

Art. no. **8223/220**
Art. no. **8223/430**

Portable diesel storage tank in polyethylene (wall thickness 5 mm), suitable for the transport in trucks or pick-ups, with ADR – approval (according to ADR 1.1.3.1.c), including refill tube, air vent valve, level gauge, forklift pockets and handles for transport (empty), equipped with electric, selfpriming pump 12 VDC (on demand also 24 VDC) with a delivery of 45 l/min, ON-/OFF-switch, automatic diesel dispensing nozzle, 4 m – rubber delivery hose 3/4" and 4 m – cable with alligator clamps for battery connection. Includes a lockable plastic cover.

Optional: electronic diesel flow meter (art. no. 2823).



Art. no. **8223/220**
Art. no. **8223/430**

Art. no.	Capacity	Weight	Dimensions (LxWxH) (mm)
8223/220	220 l	28 kg	800x600x610
8223/430	430 l	58 kg	1160x760x780



Art. no. **8224/120**
Art. no. **8224/190**

Art. no. **8224/120**
Art. no. **8224/190**

Portable petrol storage tank in high density polyethylene, electricly conductive to enable an electrostatic discharge, suitable for the transport in trucks or pick-ups, with ADR – approval (according to ADR 1.1.3.1.c), including refill tube, air vent valve, level gauge, forklift pockets and handles for transport (empty), equipped with electric, selfpriming rotary vane pump 12 VDC (on demand also 24 VDC) with a delivery of 40 l/min. (constructed in accordance with directive ATEX 94/9/EC – IECEx (group II – category 2 – G Ex d IIA T4 Gb)), 4 m – cable with alligator clamps for battery connection, 4 m – statically conductive rubber supply hose, automatic petrol dispensing nozzle and nozzle holder. Includes a lockable plastic cover.
On demand also available with manual dispensing pump.



Art. no.	Capacity	Weight	Dimensions (LxWxH) (mm)
8224/120	120 l	26 kg	800x600x470
8224/190	190 l	38 kg	800x600x610



Art. no. **8225/125** Art. no. **8225/430**
Art. no. **8225/200** Art. no. **8225/600**

Art. no. **8225/125**
Art. no. **8225/200**
Art. no. **8225/430**
Art. no. **8225/600**

Portable storage tank for AdBlue®/DEF/AUS32 in high density polyethylene, suitable for the transport in trucks or pick-ups (ADR – approval not required), including refill tube, air vent valve, level gauge, forklift pockets and handles for transport (empty), equipped with electric, selfpriming diaphragm pump 12 VDC (on demand also 24 VDC) with a delivery of 30 l/min, ON-/OFF-switch, automatic diesel dispensing nozzle, 4 m – delivery hose in EPDM, and 4 m – cable with alligator clamps for battery connection. Includes a lockable plastic cover.
Optional: electronic flow meter, suitable for AdBlue®/DEF/AUS32 (art. no. 2822).

Art. no.	Capacity	Weight	Dimensions (LxWxH) (mm)
8225/125	125 l	25 kg	800x620x470
8225/200	200 l	26 kg	800x620x610
8225/430	430 l	44 kg	1160x760x730
8225/600	600 l	52 kg	1160x800x1020

