



Art. no. 2735

Art. no. 2735

Electronic oval gears flow meter for AdBlue®, not approved for fiscal transactions, body in plastic with high density glass fibre IXEF, gears in PPS and PTFE, with plastic control gun, inlet swivel in stainless steel 1/2" BSP (M) and plastic rigid outlet, ø 16 mm, with automatic anti-drip nozzle in stainless steel.

Art. no.	Max working pressure	Max flow rate	Accuracy	Connection threads	Weight	Dimensions (LxWxH) (mm)
2735	25 bar	30 l/min	+/- 0,5%	BSP 1/2"	1,5 Kg	95x95x460



Art. no. 2166

Art. no. 2166

Plastic dispensing nozzle for AdBlue® with rigid outlet ø 16 mm, connection threads 1/2" BSP (F).

Art. no.	Max working pressure	Flow range	Connection threads	Weight	Dimensions (LxWxH) (mm)
2166	25 bar	1-30 l/min	BSP 1/2"	0,4 Kg	203x320x34



Art. no. 2689

Art. no. 2689

Electronic oval gears flow meter, body in stainless steel AISI 303, suitable for in-line applications. LCD - display with 3 different totals.

Art. no.	Max working pressure	Max flow rate	Accuracy	Connection threads	Weight	Dimensions (LxWxH) (mm)
2689	150 bar	30 l/min	+/-0,5%	BSP 1/2" (F)	1,5 Kg	165x160x80



Art. no. 2822

Art. no. 2822

Electronic turbine flow meter for AdBlue®, body in reinforced polyamide, suitable for in-line applications, with 5 - digits partial meter (resettable to zero) and 6 - digits totalizer (non resettable). The meter includes also a flow rate indicator. The display can be rotated in 4 different positions.

Art. no.	Max working pressure	Max flow rate	Accuracy	Connection threads	Weight	Dimensions (LxWxH) (mm)
2822	20 bar	100 l/min	+/-1%	1" BSP (M)	0,4 Kg	100x54x74

