

Art. no. 6738



Art. no. 6738

55 l/min

Diesel transfer kit, with electric 230 VAC – pump, mounted on wall bracket.

Composed of selfpriming electric pump with built-in bypass valve and inlet strainer, ON-/OFF switch, 2 m – cable with plug and fuse, mechanical flow meter (art. no. 2860), 4 m - rubber delivery hose 3/4", 2 m – suction hose ø 25 mm, suction foot valve with filter (art. no. 6647) and automatic nozzle with inlet swivel (art. no. 6725).

Art. no.	Voltage	Power	Current drain	Rpm	Delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
6738	230 VAC	370 W	1,5 A	2800	55 l/min	1" BSP (F)	18 Kg	400x400x290



Art. no. 6739



Art. no. 6739

100 l/min

Diesel transfer kit, with electric 230 VAC – pump, mounted on wall bracket.

Composed of selfpriming electric pump with built-in bypass valve and inlet strainer, ON-/OFF switch, 2 m – cable with plug and fuse, mechanical flow meter (art. no. 2863), 4 m - rubber delivery hose 3/4", 2 m – suction hose ø 25 mm, suction foot valve with filter (art. no. 6647) and automatic nozzle with inlet swivel (art. no. 6726).

Art. no.	Voltage	Power	Current drain	Rpm	Delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
6739	230 VAC	750 W	6,2 A	1400	100 l/min	1" BSP (F)	22 Kg	400x400x290



Art. no. 6755



Art. no. 6755

Diesel transfer kit, with electric 230 VAC – pump, mounted on wall bracket (art. no. 6739), but equipped with automatic rewind, spring – driven hose reel, adjustable arms series, in painted steel (art. no. 9095) with 8 m - rubber delivery hose 1", 2 m – connection hose to pump and diesel/water separating cartridge filter (art. no. 6600).



Art. no.	Voltage	Power	Current drain	Rpm	Delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
6755	230 VAC	750 W	6,2 A	1400	80 l/min	1" BSP (F)	42 Kg	400x400x290



Electric, centrifugal transfer pumps for diesel and fuel oil, suitable for the direct mounting on drums or tanks. These non-selfpriming pumps, protection category IP 44, include motors with thermal circuit breaker, integrated siphon protection device, ON-/OFF switch and an integrated connection thread M 64 x 4 and BSP 2". On the shaft a small manual pump is mounted which serves for the filling of the suction hose as well as for a manual pumping if there is no electric power supply available.



Art. no. **6766**
Art. no. **6768**
Art. no. **6769**

Diesel transfer kit, composed of electric 12 VDC, 24 VDC or 230 VAC pump, 3 m – cable with alligator clamps for battery connection (12 VDC and 24 VDC) or 2 m – cable with earth contact type plug (230 VAC), 1,6 m – suction hose with foot filter, 4 m – rubber delivery hose 3/4" with anti-kink spring, hose tails and manual plastic nozzle.



Optional: Electronic turbine flow meter (art. no. 2823).

Art. no.	Voltage	Power	Current drain	Delivery	Connection threads	Weight
6766	12VDC	150 W	12,5 A	31 l/min	BSP 3/4"	3,2 kg
6768	24VDC	180 W	7,5 A	34 l/min	BSP 3/4"	3,2 Kg
6769	230 VAC / 50 Hz	250 W	1,2 A	38 l/min	BSP 3/4"	3,6 kg



Art. no. **6770**
Art. no. **6771**
Art. no. **6773**

Diesel transfer kit, composed of electric 12 VDC, 24 VDC or 230 VAC pump, 3 m – cable with alligator clamps for battery connection (12 VDC and 24 VDC) or 2 m – cable with earth contact type plug, 1,6 m – suction hose with foot filter, 4 m – rubber delivery hose 3/4" with anti-kink spring, hose tails and automatic dispensing nozzle with inlet swivel.



Optional: Electronic turbine flow meter (art. no. 2823).

Art. no.	Voltage	Power	Current drain	Delivery	Connection threads	Weight
6770	12 VDC	150 W	12,5 A	31 l/min	BSP 3/4"	4,1 kg
6771	24 VDC	180 W	7,5 A	34 l/min	BSP 3/4"	4,1 Kg
6773	230 VAC / 50 Hz	250 W	1,2 A	38 l/min	BSP 3/4"	4,5 kg



Art. no. **6782**
Art. no. **6783**

Electric, hybrid transfer pumps for diesel, fuel oil, bio-diesel (with suitable hoses), antifreeze (with or without water), suitable for the direct mounting on drums or tanks. These pumps are selfpriming, protection category IP 54, with ON-/OFF switch and an integrated connection thread BSP 2".

Art. no. **6782**

Diesel transfer kit, composed of electric 230 VAC pump, 4 m – cable with earth contact type plug, 1,6 m – suction hose with foot filter, 4 m – rubber delivery hose 3/4", high delivery automatic nozzle with inlet swivel, with electronic in-line turbine flow meter (art. no. 2823).



Art. no. **6783**

Diesel transfer kit, same as art. no. 6782, but without electronic in-line turbine flow meter.

Art. no.	Voltage	Power	Current drain	Delivery	Connection threads	Weight
6782	230 VAC / 50 Hz	950 W	4,5 A	80 l/min	BSP 1"	4,5 kg
6783	230 VAC / 50 Hz	950 W	4,5 A	85 l/min	BSP 1"	4,1 Kg