



Art. no. **6252**  
Art. no. **6254**

Art. no. **6252**  
Art. no. **6254**

**43 l/min**

Electric vane pump, 12 VDC and 24 VDC, selfpriming, for the transfer of diesel, with transport handle, ON-/OFF-switch and 2 m – cable with alligator clamps for battery connection.

Art. no.	Voltage	Power	Current drain	Rpm	Delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
<b>6252</b>	12 VDC	216 W	18 A	2800	43 l/min	1" BSP (F)	4,5 Kg	140x150x200
<b>6254</b>	24 VDC	240 W	9 A	2800	43 l/min	1" BSP (F)	4,5 Kg	140x150x200



Art. no. **6253**  
Art. no. **6255**

Art. no. **6253**  
Art. no. **6255**

**60 l/min**

Electric vane pump, 12 VDC and 24 VDC, selfpriming, for the transfer of diesel, with transport handle, ON-/OFF-switch and 4 m – cable with alligator clamps for battery connection.

Art. no.	Voltage	Power	Current drain	Rpm	Delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
<b>6253</b>	12 VDC	240 W	30 A	4200	60 l/min	1" BSP (F)	5,6 Kg	130x150x300
<b>6255</b>	24 VDC	240 W	15 A	4200	60 l/min	1" BSP (F)	5,6 Kg	130x150x300



Art. no. **6256**  
Art. no. **6257**

Art. no. **6256**  
Art. no. **6257**

**85 l/min**

Electric vane pump, 12 VDC and 24 VDC, selfpriming, for the transfer of diesel, with transport handle, ON-/OFF-switch and 4 m – cable with alligator clamps for battery connection. Bypass valve included in pump body.



Art. no.	Voltage	Power	Current drain	Rpm	Delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
<b>6256</b>	12 VDC	400 W	40 A	2000	85 l/min	1" BSP (F)	10,4 Kg	190x350x280
<b>6257</b>	24 VDC	400 W	25 A	2000	85 l/min	1" BSP (F)	10,4 Kg	190x350x280





Art. no. 6230

Art. no. **6230**

Electric eccentric pump, 12 VDC, selfpriming, for the transfer of diesel, encased, with transport handle, suction foot valve with filter, ON-/OFF-switch and 2 m – cable with alligator clamps for battery connection.

Delivery 30 l/min at free flow outlet.

This pump can also work with 24 VDC and a delivery of 30 l/min for max 15 min.

The max suction lift is 3 m, the bypass is set at 1 bar.

**30 l/min**

Art. no.	Voltage	Power	Current drain	Rpm	Delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
<b>6230</b>	12 VDC	192 W	16 A	1300	30 l/min	hose tails ø 25 mm	7 Kg	300x120x200



Art. no. 6245

Art. no. **6245**

Electric vane pump, 12 VDC, selfpriming, for the transfer of diesel, encased, with transport handle, suction foot valve with filter, ON-/OFF-switch and 2 m – cable with alligator clamps for battery connection.

This pump can also work with 24 VDC and a delivery of 60 l/min for max 15 min.

Delivery 45 l/min with 12 VDC at free flow outlet.

**45 l/min**  
**60 l/min**



Art. no. **6248**

Same as art. no. 6245, but with mechanical flow meter (art. no. 2860).

Art. no.	Voltage	Power	Current drain	Rpm	Delivery	Connections	Weight	Dimensions (LxWxH) (mm)
<b>6245</b>	12 VDC	400 W	40 A	3000	45 l/min	hose tails ø 25 mm	7,5 kg	130x150x360
<b>6248</b>	12 VDC	400 W	40 A	3000	45 l/min	hose tails ø 25 mm	8,7 kg	130x150x510



Art. no. 6246  
Art. no. 6249

Art. no. **6246**  
Art. no. **6249**

Diesel transfer kit, mounted on wall bracket. Available with motor in 12 VDC or 24 VDC.

Composed of mechanical flow meter (art. no. 2860), selfpriming electric vane pump (art. nos. 6252 or 6254) with built-in bypass valve and inlet strainer, ON-/OFF switch, 2 m – cable with alligator clamps for battery connection, suction foot valve with filter (art. no. 6647), 4 m - rubber delivery hose 3/4" and manual aluminium nozzle.



**Optional:** automatic nozzle with inlet swivel (art. no. 6725).

Art. no.	Voltage	Power	Current drain	Rpm	Delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
<b>6246</b>	12 VDC	220 W	18 A	2800	43 l/min	1" BSP (F)	14 Kg	430x160x340
<b>6249</b>	24 VDC	240 W	9 A	2800	43 l/min	1" BSP (F)	14 Kg	430x160x340

