

Portable and wall-mounted pneumatic and electric pumps for the transfer of diesel. The indicated delivery figures refer on a free flow outlet.



Art. no. **6557**

35 l/min

Pneumatic, rotary vane pump for the transfer of diesel, with filter and bypass valve, body in aluminium.

Art. no.	Compressed air supply	Air consumption	Outlet pressure	Max delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
6557	4 bar	160 l/min	4 bar	35 l/min	3/4" BSP (F)	5 Kg	140x150x190



Art. no. **6556**

30 l/min

Diesel transfer kit, composed of pneumatic, rotary vane pump, art. no. 6557, suction tube with foot valve suitable for 208 l – drums, bung adapter for the fixation of the pump on the drum, 4 m – delivery hose 3/4" and manual aluminium nozzle.



Art. no.	Compressed air supply	Air consumption	Outlet pressure	Max delivery	Connection threads	Weight
6556	4 bar	160 l/min	4 bar	30 l/min	3/4" BSP (F)	12 Kg



Art. no. 6772

25 l/min

Diesel transfer kit, composed of pneumatic 1:1 - piston pump, standard series, with wall bracket (art. no. 2044), pressure regulator with manometer and air filter, 1,5 m rubber suction hose \varnothing 1" BSP with foot valve and filter, electronic in-line turbine flow meter (art. no. 2823), 4 m - rubber delivery hose 3/4" and automatic nozzle with inlet swivel (art. no. 6725).

Optional: diesel/water separating cartridge filter (art. no. 6600), see page 160.

Art. no.	Compressed air supply	Compression ratio	Max outlet pressure	Max delivery	Outlet connection threads	Weight
6772	2 - 8 bar	1 : 1	8 bar	25 l/min	BSP 3/4"	13 kg



Art. no. 6776

100 l/min

Diesel transfer kit, composed of pneumatic 1,5:1 - piston pump, series Power Bull (art. no. 2098), delivery 100 l/min., with wall bracket (art. no. 2214/110), pressure regulator with manometer and air filter, 1,5 m rubber suction hose \varnothing 1" BSP with foot valve and filter, electronic in-line turbine flow meter (art. no. 2823), 4 m - rubber delivery hose 1" and high delivery automatic nozzle with inlet swivel (art. no. 6726).

Optional: diesel/water separating cartridge filter (art. no. 6600), see page 160.

Art. no.	Compressed air supply	Compression ratio	Max outlet pressure	Max delivery	Outlet connection threads	Weight
6776	1 - 8 bar	1 : 1	8 bar	100 l/min	BSP 1"	46 kg