

Adblue® Kit NEW

[IT] Gruppo portatile per travaso AdBlue®.

[EN] Portable AdBlue® DEF transfer unit.



codice prodotto product code	Voltaggio Voltage
	V
ADBLUEKIT12V	12
ADBLUEKIT24V	24



Gruppo portatile per travaso AdBlue®, corredato di elettropompa a batteria con motore a 12 V o 24 V a corrente continua.

Grazie alla sua compattezza, affidabilità e facilità di utilizzo, trova impiego in tutti quei casi in cui è richiesta l'erogazione o il travaso di urea in condizioni di sicurezza e quando è disponibile solamente un'alimentazione elettrica a batteria.

Tipici campi di utilizzo di questo kit di travaso sono il rifornimento delle macchine agricole a autotrasporto.

Portable unit for AdBlue® DEF transfer, fitted with battery pump, 12 V or 24 V, suction and delivery hoses, filter and fuel nozzle.

Thanks to its small size, reliability and ready-to-use configuration, it is especially useful when fuel must be transferred or dispensed safely having only battery power on hand. Typical fields of application are agriculture and transport.

PRESTAZIONI E DIMENSIONI:

- Alimentazione: 12 V o 24 V dc.
- Assorbimenti: 22 Amp a 12 V dc - 11 Amp a 24 V dc.
- Portata: 40 L/min.
- Capacità d'aspirazione fino a 1,5 metri di altezza.
- Ciclo di lavoro: 30 min.
- Temperatura di lavoro: -20° C / +60° C.
- Dimensioni: 600x420x230h mm

PERFORMANCES AND DIMENSIONS:

- Power supply: 12 V DC or 24 V DC.
- Consumption: 22 Amp (12 V DC) - 11 Amp (24 V DC).
- Max flow rate: 40 L/min.
- Suction height: up to 1,5 meters.
- Working temperature: -20°C / +60°C.
- Duty cycle: 30 min.
- Dimensions: 600x420x230h mm

CARATTERISTICHE COSTRUTTIVE:

- Pompa rotativa a membrana, autoadescente con by-pass integrato.
- Morsettiera per alloggiamento interruttore e fusibile per protezione da sovraccarichi.
- Cavi di lunghezza 4 metri con pinza per collegamento a batteria.
- Tubo in gomma in EPDM, lunghezza 3 metri, diametro 3/4".
- Filtro di fondo per tubo di aspirazione.
- Tubo di aspirazione lungo 3 metri.
- Pistola manuale in plastica.

TECHNICAL FEATURES:

- Self-priming volumetric diaphragm vane pump, with by-pass valve.
- Terminal board for switches and circuit-breakers.
- Battery cable, 4 m length, complete with clamps for battery connection.
- EPDM hose, 3 m length, size 3/4", suitable for AdBlue® DEF.
- Aluminium manual nozzle.
- Suction fuel hose, 3 m length, size 3/4", suitable for AdBlue® DEF.
- Bottom suction filter.
- Manual nozzle for AdBlue® DEF.