



Squeezing Type Peristaltic Pump for Grouting Works

Type	TS-23MTG(PC)
Power	1.5 kW*200 V Three Phase
Speed Control	Inverter Control
Discharge Volume	13.5-31.5 L/min(6-22.5 L/min)
Max. Pressure	25 kgf/cm ²
Capacity	Horizontal 85m or Vertical 25m (Horizontal 150m or Vertical 50m)
Pumping Tube	Dia.40*L1250
Pumping Roller	3 Pumping Rollers
Dimensions	W480*L1140*H630mm
Weight	155 kg

- Electrical systems can be converted for your countries' conditions.



Squeezing Type Peristaltic Pump for Grouting Works

Type	TS-53MTG-4(PC)
Power	3.7 kW*200 V Three Phase
Speed Control	Inverter Control
Discharge Volume	31.5-45 L/min(6-40 L/min)
Max. Pressure	25 kgf/cm ²
Capacity	Horizontal 120m or Vertical 30m (Horizontal 200m or Vertical 60m)
Pumping Tube	Dia.40*L1250
Pumping Roller	3 Pumping Rollers
Dimensions	W540*L1270*H640mm
Weight	200 kg

- Electrical systems can be converted for your countries' conditions.



Squeezing Type Peristaltic Pump for Grouting Works

Type	TS-73MTG
Power	5.5 kW*200 V Three Phase
Speed Control	Inverter Control
Discharge Volume	45-90 L/min
Max. Pressure	25 kgf/cm ²
Capacity	Horizontal 150m or Vertical 40m
Pumping Tube	Dia.50*L1400
Pumping Roller	3 Pumping Rollers
Dimensions	W560*L1330*H800mm
Weight	300 kg

- Electrical systems can be converted for your countries' conditions.