



WATER SUCTION/DISCHARGE HOSE



WSD150 150 PSI

WATER SUCTION/DISCHARGE HOSE

Water Suction & Discharge hose suitable for a variety of general purposes in industries, construction sites and mines. It handles sewage, waste water, mud & etc.

TEMPERATURE RANGE: - 40°C to + 85°C

TUBE: Black, smooth, synthetic rubber resistance to water with PH Value 5~8

REINFORCEMENT: High tensile synthetic cord and a helix wire

COVER: Black, smooth (wapped finish) synthetic rubber, abrasion & weathering resistant

COILS: 40mt length; other length, size and color available on request

BRANDING: Purple transfer tape with white text

'TECHFLEX WSD 150 WATER SUCTION/DELIVERY HOSE WPSI 150 '

Part No	I.D		O.D		Working Pressure		Bursting Pressure		Weight
	mm	inches	Mm	inches	Atm	Psi	Atm	Psi	
WS150-125	32	1-1/4	43	1.21/32	10	150	30	450	0.97
WS150-150	38	1-1/2	50	2.15/16	10	150	30	450	1.27
WS150-200	51	2	63	2.15/32	10	150	30	450	1.72
WS150-250	63	2-1/2	77	3-1/32	10	150	30	450	2.37
WS150-300	76	3	89	3-1/2	10	150	30	450	2.79
WS150-400	102	4	118	4-9/16	10	150	30	450	4.33
WSD150-500	127	5	144	5-5/8	10	150-	30	450	7.23
WSD150-600	152	6	171	6-3/4	10	150	30	450	10.18
WSD150-800	203	8	227	8-15/16	10	150	30	450	14.80
WSD150-1000	254	10	280	11-1/8	10	150	30	450	16.34
WSD150-1200	305	12	336	13-15/64	10	150	30	450	24.63