



“MP” Manual Hoist



Lever Hoist

Optional Features:

- Overload protection system.
- Caged ball bearing on load sheaves.
- Cast safety latches.
- Thrust bearings in bottom hook assembly.
- Load chain is made by steel alloy grade 80 accord with EN818-7 standard.
- Special surface treatment of spare parts.

Capacity (tons)	Load Chain (mm)	Standard Lift (m)	Rated Load (N)	Running Test Load (KN)	Weight (kg)
0.75	6x18	1.5	140	9.2	6.3
1.5	8x24	1.5	220	18.4	11
3	10x30	1.5	320	36.8	16.7
6	10x30	1.5	340	73.5	30
9	10x30	1.5	360	110.3	41.2

Capacity (tons)	Load Chain (mm)	Standard Lift (m)	Rated Load (N)	Running Test Load (KN)	Weight (kg)
0.5	6x18	3	200	6.13	8.7
1	6x18	3	320	12.25	10.8
1.5	8x24	3	360	18.38	15.2
2	8x24	3	365	24.5	18
3	8x24	3	385	38.75	24.3
5	10x30	3	435	61.25	38.7
10	10x30	3	435	122.5	78
20	10x30	3	435x2	245	163.6
30	10x30	3	435x2	367.5	220
50	10x30	3	435x2	812.5	1092



Chain Hoists