

# S MANUAL NOZZLES SELF



**EN.** Manual nozzles. These nozzles, distinguished by high efficiency, based on low flow resistance, remarkably easy use and of reasonable cost, are designed to be used with any type of transfer system, even those run by gravity. Supplied complete with removable lever protection, a variety of threaded connectors and a reduced section tube for unleaded gasoline.

**ES.** Pistolas manuales. Se caracterizan por su eficiencia y la resistencia en caudal bajo, facilidad de uso y precio económico. Dadas sus características, encuentran fácil instalación en todo tipo de instalaciones de trasiego, incluso en las que funcionan con gravedad. Se proveen completos con protección de palanca removible, una variedad amplia de enrosques de para diferentes conexiones u tubo de sección reducida para la gasolina.

**PT.** Pistolas manuais. Caracterizam-se por uma alta eficiência por causa da baixa resistência ao fluxo juntamente com uma notável simplicidade na utilização e economia. Por causa das suas características, podem ser aplicadas em qualquer tipo de sistema de transferência, mesmo os que funcionam por gravidade. São fornecidas equipadas com bloqueio do gatilho, que pode ser solto, e são disponíveis com vários engates com rosca e com tubo de pequeno diâmetro para gasolina verde.

## PERFORMANCE

Flow rate up to 150 l/min

Caudal de hasta 150 l/min

Caudal até 150 l/min



## PRODUCTS' RANGE WEIGHT

Code	Weight	
	kg	lbs
F00641130	0,7	1,5
F0065000A	0,6	1,3
00065001A	0,6	1,3
F0063001A	0,2	0,4
F0063000A	0,2	0,4

**Flow-rate**  
up to  
**150** l/min  
(up to 40 gpm)



SELF 2000 DIESEL



SELF 3000 DIESEL/GASOLINE



PLASTIC NOZZLE-S WATER/DIESEL



PLASTIC NOZZLE WATER/FOOD



UREA NOZZLE (available)

## FEATURES



Swivel

Not included in the Plastic nozzle model

## PRODUCTS' RANGE TECHNICAL DATA

Code with swivel	Description	Fluid type	Flow-rate		Inlet		Spout ext. Ø mm
			l/min	gpm	swivel BSP	with swivel BSP	
F00641130	* Self 2000 1"	B D G O	120	32	YES	F 1"	25
F0065000A	* Self 3000 1"	B D G O	150	40	YES	F 1"	25
00065001A	* Self 3000 1" unleaded spout	B D G O	150	40	YES	F 1"	20
F0063001A	Plastic nozzle 1" (water/food version)	B D G O W	80	21	NO (Hose tail 1")	F 1"	34
F0063000A	Plastic nozzle-S 1"	B D G O W	80	21	YES	F 1"	34

DISPENSERS

PUMPS

METERS

NOZZLE METERS

NOZZLE

SPECIAL EQUIPMENTS

FLUID MONITORING

ACCESSORIES

FILTERING



# AUTOMANTIC NOZZLES

## A60 - A80 - A120 - A280

**EN.** Automatic nozzles. These nozzles are fitted with a device that automatically shuts off flow when the tank is full. Complete with swivel connector they conform to the strictest safety requirements and bear all necessary certifications.

**ES.** Pistolas automáticas. Equipadas con un dispositivo de parada de flujo automático. Racor giratorio, están a la par con los requisitos de seguridad más severos y cuentan con todas las certificaciones necesarias.

**PT.** Pistolas automáticas. São equipadas com um dispositivo de paragem automática do fluxo quando o depósito encher-se. Equipadas com união giratória atendem aos mais severos requisitos de segurança e receberam as certificações necessárias.

### PERFORMANCE

Flow rate up to 280 l/min

Caudal de hasta 280 l/min

Caudal até 280 l/min

### PRODUCTS' RANGE WEIGHT AND PACKAGING

Code	Weight	
	kg	lbs
F00603060	1.25	2,76
F00602020	1.20	2,65
F00604030	1.93	4,25
F00610020	1.93	4,25
F13249000	3.3	7,28
F00613A00	1.30	2,87
F00614000	1.65	3,64
F00602030	1,25	2,76
F0061903B	2,60	5,73
F00613020	1,25	2,76



ANTIFREEZE  
BIO DIESEL  
DIESEL  
FOOD  
GASOLINE  
GREASE  
KEROSENE  
OIL  
UREA  
WATER  
WINDSCREEN

**Flow-rate**  
up to  
**280** l/min  
(up to 74 gpm)



A60



A80



A120



A280


**FEATURES**



Automatic stop




High flow rate



Swivel

**ON REQUEST**



Rapsoil version



Urea version



Automatic nozzle

Code F00613020

**PRODUCTS' RANGE TECHNICAL DATA**

Code without swivel	Code with swivel	Description	Fluid type	Flow-rate		Inlet		Spout ext. Ø mm
				l/min	gpm	without swivel BSP	with swivel BSP	
F12127000	F00603060	A60	DG	70	19	F 3/4"	F 1"	24
F1244200A	F00602020	A60 Unleaded	DG	60	16	F 3/4"	F 1"	20
F12449000	F00604030	A80	DG	90	24	F 1"	F 1"	29
F12128000	F00610020	A120	DG	120	32	F 1"	F 1"	29
-	F13249000	A280	DG	280	74	-	1 1/2"	38,5
-	F00613A00	A60 - EN 13012	D	70	19	F 3/4"	F 1"	24
-	F00614000	A120 - EN 13012	D	120	32		F 1"	29
F00602040	F00602030	Autom. Nozzle RAPSOIL	B	60	16	F 3/4"	F 1"	24
-	F0061903B	Autom. Nozzle UREA (inox)	WU	40	11	-	F 3/4"	19
-	F00613020	Autom. Nozzle ATEX	DGK	60	16	-	F 1"	20