



“JK” Oil Free Compressor -Medical



1

Model								dB		Dimension
	Liter	c/st	l/min	bar	kW	HP	V			
JK-24.F114	28	1/1	100	8	0,75	1,0	230	72	35	480 x 460 x 750
JK-24.GMS150	28	1/1	150	8	1,10	1,5	230	75	40	480 x 460 x 665
JK-24.GMS150D	28	1/1	150	8	1,10	1,5	230	75	45	480 x 460 x 655
JK-24.VS204	28	2/1	200	8	1,50	2,0	230	75	45	480 x 460 x 670
JK-24.VS204D	28	2/1	200	8	1,50	2,0	230	75	50	480 x 460 x 670
JK-50.VS204	50	2/1	200	8	1,50	2,0	230	75	50	480 x 460 x 840
JK-50.VS204D	50	2/1	200	8	1,50	2,0	230	75	55	655 x 460 x 830
JK-100.VS204T	100	2/1	400	8	1,5+1,5	2+2	230	79	105	1140 x 440 x 865
JK-100.VS204TD	100	2/1	400	8	1,5+1,5	2+2	230	79	110	1140 x 440 x 865
JK-24.VS254	28	2/1	250	8	1,80	2,4	230	75	45	480 x 460 x 670
JK-24.VS254D	28	2/1	250	8	1,80	2,4	230	75	50	480 x 460 x 670
JK-50.VS254	50	2/1	240	8	1,80	2,4	230	75	50	480 x 460 x 840
JK-50.VS254D	50	2/1	240	8	1,80	2,4	230	75	55	655 x 460 x 840
JK-100.VS254T	100	2/1	500	8	1,8+1,8	2,4+2,4	230	79	105	1140 x 440 x 865
JK-100.VS254TD	100	2/1	500	8	1,8+1,8	2,4+2,4	230	79	110	1140 x 440 x 865



Model								dB		Dimension
	Liter	c/st	l/min	bar	kW	HP	V			
JK-8.F114K	8	42370	100	8	0,75	1,0	230	57	45	760 x 400 x 615
JK-16.GMS150K	16	42370	150	8	1,10	1,5	230	57	80	515 x 640 x 800
JK-16.GMS150KD	16	42370	150	8	1,10	1,5	230	57	85	515 x 640 x 800
JK-16.VS204K	16	42401	200	8	1,50	2,0	230	65	85	515 x 615 x 800
JK-16.VS204KD	16	42401	200	8	1,50	2,0	230	65	87	515 x 615 x 800



“JK” Oil Free Compressor -Industrial Series



2,2 kW

MODEL	Lt	C/St	l/min	bar	kW	V	kg	Dimensions A x B x C, mm
JK 4-F22	-	2/1	420	10	2,2	230/400	67	900 x 550 x 700
JK 4-100.F22	100	2/1	420	10	2,2	230/400	88	1180 x 500 x 1000

2



4,0 kW

5,5 kW

MODEL	Lt	C/St	l/min	bar	kW	V	kg	Dimensions A x B x C, mm
JK 4-F37	-	2/1	675	10	4,0	400	101	1100 x 600 x 700
JK 4-270.F37	270	2/1	675	10	4,0	400	180	1670 x 600 x 1200
JK 4-F55	-	2/2	690/560	10/14	5,5	400	130	1100 x 600 x 740
JK 4-500.F55	500	2/2	690/560	10/14	5,5	400	250	2000 x 620 x 1440



7,5 kW

11,0 kW



MODEL / Typ	Lt	C/St	l/min	bar	kW	V	kg	Dimensions Abmessungen A x B x C, mm
JK 4-F75	-	3/2	1120/900	10/14	7,5	400	158	1100 x 625 x 780
JK 4-500.F75	500	3/2	1120/900	10/14	7,5	400	315	2000 x 620 x 1440
JK 4-F110	-	3/2	1620/1300	10/14	11,0	400	180	1100 x 620 x 820
JK 4-500.F110	500	3/2	1620/1300	10/14	11,0	400	337	2000 x 620 x 1440



“JK” Oil Free Compressor

-Compressors With Low Noise Pump TWIN Cylinder



0,75 kW

1,1 kW

1,4 kW

1,1+1,1 kW

1,4+1,4 kW

3



MODEL	Lt	C/St	l/min	bar	kW	V	db	kg	Dimensions A x B x C, mm
JK4/C-24.OLD10	24	2/1	105	8	0,75	230	65	28	595 x 300 x 600
JK4/C-24.OLD15	24	2/1	150	8	1,1	230	68	34	595 x 300 x 660
JK4/C-24.OLD20	24	2/1	200	8	1,4	230	68	36	595 x 300 x 660
JK4/C-50.OLD15	50	2/1	150	8	1,1	230	68	44	840 x 445 x 740
JK4/C-50.OLD20	50	2/1	200	8	1,4	230	68	46	840 x 445 x 740
JK4-100.OLD15T	100	2/1	300	8	1,1+1,1	230	72	88	1180 x 420 x 900
JK4-100.OLD20T	100	2/1	400	8	1,4+1,4	230	72	89	1180 x 420 x 900

