


# Wet and Dry Diamond Core Drills - Electric

## Hand-Held and Rig-Mounted Core Drills

- Drill holes from 5/32" to 18" dia. in floors, walls and ceilings
- Fast drilling of reinforced concrete, concrete, brick, block and stone
- 5/8" and 1-1/4" standard thread connections
- Drills are equipped with a "slip clutch"
- Wet/Dry models have dust collection port

*Wet and Dry Diamond Core Bits available for concrete, stone, asphalt and more. Contact us for details.*



**Wet - 3-speed**  
END 130/3 PO  
END 130/3 POSA  
END 130/3 POSV  
Drill holes up to 6"



END 130/3POSV



**Wet/Dry - 2-speed**  
ETN 2001 P  
ETN 2001 PSA  
ETN 2001 PSV  
Drill holes up to 4"



**Wet/Dry - 3-speed**  
ETN 162/3 P  
ETN 162/3 PSA  
ETN 162/3 PSV  
Drill holes up to 6"

Model No.	Motor Power (Amps)	Drilling Diameter	Load Speed (RPM)	Weight (lbs.)*	Drill with Anchor Stand Model No.	Drill with Anchor Stand & Vacuum Pump Model No.
END 712 P	6.3	5/32" to 3/4"	0-8000	5	N/A	N/A
END 1550 P	13	1/4" to 2-5/8"	1800-4400	7	N/A	N/A
ETN 2001 P	15	up to 4"	0-800/0-1570	15	ETN 2001 PSA	ETN 2001 PSV
ETN 162/3 P	19	up to 6"	0-510/0-1150/0-2500	15	ETN 162/3 PSA	ETN 162/3 PSV
END 130/3 PO	15	up to 6"	600/1300/2800	16	END 130/3 POSA	END 130/3 POSV
EBM 350/3 P	24.5	up to 14"	230/500/1030	28	EBM 350/3 PSA	EBM 350/3 PSV
DBE 160	18	up to 6"	700	34**	Included	N/A

\* Weight is for hand-held models only. Please contact CS Unitec for weight information on drill rig combinations.

\*\* Weight is for the complete drill rig.

Note: Hand-held core drills are intended up to a max. of 3" dia. for hand-held drilling or up to 6" dia. with a stand.



**1-speed**  
DBE 160  
Rig-mounted  
Drill holes up to 6"

**3-speed**  
EBM 350/3 P (motor only, for use with compatible stands)  
EBM 350/3 PSA (anchor stand)  
EBM 350/3 PSV (anchor vacuum stand)  
Drill holes up to 14"

**END 1550 P**  
Ideal for stone, tiles, ceramic, porcelain, stoneware, glass, reinforced concrete and more  
Drill holes up to 2-5/8"  
1800-4400 RPM  
Swivel anchor stand available: BST 50V



**END 712 P**  
Mini Diamond Drill for tile, natural stone and concrete  
Drill holes 5/32" to 3/4"  
0-8000 RPM



Wet



# Dry Diamond Core Drills and Stands

## Core Drill Stands



360° swivel range

**BST 50V**  
Anchor Stand,  
17" high,  
16 lbs.



**BST 85**  
Anchor Stand,  
31" high,  
16 lbs.



**BST 104/60V**  
Anchor Vacuum  
Stand, 30" high,  
21 lbs.



**BST 162 V**  
Anchor Vacuum  
Stand, 38" high,  
31 lbs.



**BST 300**  
Anchor Stand,  
44" high,  
45 lbs.



**BST 300 V**  
Anchor Vacuum  
Stand, 44" high,  
50 lbs.



## Water Recycling and Slurry Containment Vacuum

- Ideal for wet-working tools such as diamond core drills, tile saws and wet grinders
- Slurry and debris are contained in filter bag
- Continuous loop system returns clean water back into the vacuum for delivery back to the tool
- Can also be used as a regular wet/dry vacuum and to pump water from one location to another

CS 2000 shown with  
END 130/3POSV  
Core Drill and Water  
Collection Ring.



### CS 2000

<b>Power</b>	17 Amp, 115 VAC/60Hz
<b>Water Capacity</b>	7 gallons
<b>Pump Output</b>	78 GPM at ground level
<b>Water Lift</b>	18 ft. max. discharge height
<b>Water Pressure</b>	14.5 PSI (pump delivery)
<b>Air Flow</b>	150 CFM
<b>Canister Volume</b>	13 gallons
<b>Canister</b>	Stainless steel tank with cart
<b>Dimensions</b>	20.5" W x 21.6" L x 39.5" H
<b>Weight</b>	59 lbs.
<b>Slurry Filter Bags</b>	P/N 420592

### Water Collection Rings

#### Part No. Description

35875	Water Collection Trap Ring for BST 104/60 V
3587A	Water Collection Trap Ring for BST 162 V
35879	Water Collection Trap Ring for BST 300 and BST 300 V
35849	Water Collection for Hand-Held Drilling (ETN 2001 P)
35847	Water Collection for Hand-Held Drilling (END 130/3PO and ETN 162/3P)
255.036	Water Collection for Hand-Held Drilling (2 1320, 2 1333, 2 1335 and 2 1317)

## Hand-Held Dry Core Drilling



**EHD 1300**  
Drill holes  
up to 3-1/4"



**EHD 2000**  
Drill holes  
up to 5"


Model No.	Motor Power (Amps)	Drilling Diameter	Load Speed (RPM)	Weight (lbs.)
<b>EHD 1300</b>	12	up to 3-1/4"	0-2000	7
<b>EHD 2000</b>	15	up to 5"	0-1000/0-2000	13

# Wet Diamond Core Drills - Hydraulic and Air

## Hydraulic Core Drills

- Rugged 3-speed gearbox with mechanical slip clutch
- Ideal for heavy-duty wet drilling in concrete, reinforced concrete and asphalt
- Self-regulating oil flow control – required volume of 6 GPM; flow up to 13 GPM is automatically bypassed back to the tank
- Hose diameter: 1/2" ID Hose with 3/8" FF (HTMA) Couplings

Model No.	Motor Power (HP)	Max. Drilling Dia.	Free Speed (RPM)	Connecting Threads	Oil Flow/ 2000 PSI	Weight (lbs.)	Stand
<b>2 1317 0030*</b>	3.6	6"	380/900/1800	1-1/4"x7 UNC Male 5/8"x11 UNC Male G 1/2" Female	6 GPM	16	N/A*
<b>2 1327 0010 SA</b>	4.2	12"	380/900/1800	1-1/4"x7 UNC Male G 1/2" Female Optional: 5/8"x11	6 GPM	69	Anchor Stand
<b>2 1327 0010 SV</b>	4.2	12"	380/900/1800	1-1/4"x7 UNC Male G 1/2" Female Optional: 5/8"x11	6 GPM	82	Anchor Stand and Vacuum Pump



Model  
2 1317 0030




Model  
2 1327 0010 SA

Note: Hand-held core drills are intended up to a max. of 3" dia. for hand-held drilling or up to 6" dia. with a stand.

\* For Drill Rig with Anchor Stand, Order No. 2 1317 0030 SA; for Drill Rig with Anchor Stand and Vacuum Pump, Order No. 2 1317 0030 SV

## Pneumatic Core Drills

- Rugged 3-speed gearbox with mechanical slip clutch
- Ideal for heavy-duty wet drilling in concrete, reinforced concrete and asphalt
- Pneumatic power for hazardous areas and Ex zones



Model 2 1333 0010



Model 2 1328 0050 SA

Model No.	Motor Power (HP)	Max. Drilling Dia.	Load Speed (RPM)	CFM@ 90 PSI	Weight (lbs.)	Stand
<b>2 1333 0010</b>	2.1	3"	400/900/1600	77	18	N/A
<b>2 1333 0010 SA</b>	2.1	6"	400/900/1600	77	49	Anchor Stand
<b>2 1333 0010 SV</b>	2.1	6"	400/900/1600	77	51	Anchor Stand & Vacuum Pump
<b>2 1335 0010</b>	3.8	3"	300/700/1350	123	21	N/A
<b>2 1335 0010 SA</b>	3.8	6"	300/700/1350	123	52	Anchor Stand
<b>2 1335 0010 SV</b>	3.8	6"	300/700/1350	123	54	Anchor Stand & Vacuum Pump
<b>2 1328 0050 SA</b>	3.8	12"	300/700/1350	123	66	Anchor Stand
<b>2 1328 0050 SV</b>	3.8	12"	300/700/1350	123	72	Anchor Stand & Vacuum Pump

Note: Hand-held core drills are intended up to a max. of 3" dia. for hand-held drilling or up to 6" dia. with a stand.

## Power Packs

### Hydraulic Power Unit

#### Model P95

- Ideal for use with our hydraulic power tools
- Delivers 5 GPM or 8 GPM at 2000 PSI
- Easy to move with lift and latch handle
- Weighs 330 lbs.



### AirPac Dryer/Cleaner

#### Model CSAP-2

- Removes moisture and dirt from air lines; a float valve automatically ejects water and dirt
- Includes automatic oiler; protects tools from freezing in cold environments
- Eliminates air motor downtime caused by water and dirt
- Connections for two tools, max. air flow 185 CFM



#### Air Tool Lubricant

ProLube-ATL - P/N CS 7043-001 (gallon)

#### Air Tool Lubricant with Anti-Freeze

ProLube-ATL/AF - P/N CS 7049-001 (gallon)

#### Air Tool Line Conditioner/Cleaner

For use in underwater air tools – displaces moisture and inhibits rust and corrosion of air motors - P/N MS 9105 (quart)