



803

Tracked Conventional Tail Excavators



Compact and Powerful - 803

The 803 is the smallest Wacker Neuson excavator and is ideally suited for demolition and excavating in tight spaces. Its compact size, at just 27.5 in/700 mm wide, makes it ideal for work in buildings. The rubber tracks do not damage floors and it can easily drive through interior doors. The 803 features foldable ROPS compliant with TOPS and ROPS regulations. Hydraulic system features twin pump and hydraulic oil cooler. Mechanical joystick controls and ISO/SAE control pattern changeover. Two-way auxiliary hydraulics with non-pressurized return to tank.

- The 3-cylinder diesel engine is powerful, efficient and reliable.
- Robust design, hydraulic oil cooler and direct to tank auxiliary hydraulics are engineered to operate the NE6 Wacker Neuson hammer.
- The stabilization blade extensions stays connected to the machine to ensure they are not lost.
- Foldable ROPS for accessibility through interior door frames
- The extended hydraulic telescopic chassis gives added stability.

wackerneuson.com - 06.08.2015 Page: 1/3





Technical specifications

Operating data

Shipping weight min.	2,050 lb
Operating weight min.	2,271 lb
Biting force max.	1,012 lbf
Breakaway force	2,000 lbf
Digging depth	68 in
Dumping height max.	80 in
Digging radius	121 in
LxWxH*	108 x 28 x 59 in

Engine / Motor

Engine / Motor manufacturer	Yanmar
Engine / Motor type	3TNV70
Engine / Motor	Water-cooled 3-cylinder diesel engine
Displacement	52 in ³
RPM / speed	2,100 rpm
Engine performance acc. to ISO	13 hp
Battery	20 Ah
Tank capacity	11 US qt

Hydraulic system

Duty pump	2 gear pumps 6 US gpm	
Flow rate		
Operating pressure for working and traction hydraulics	2,466 psi	
Operating pressure Slewing gear	1,015 psi	
RPM / speed Superstructure	8 rpm	
Hydraulic oil tank	15 US qt	

Wheel set

Travel speed	1.1 mph
Gradeability	58 %
Chain width	7.1 in

wackerneuson.com - 06.08.2015 Page: 2/3





Ground clearance	5 in	
Dozer Blade		
Width min.	28 in	
Height	7.9 in	
Sound level		
Sound level (LwA) acc. to 2000/14/EC	9	3 dB(A)

^{*} Without ROPS bar

Please note

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions.

Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2015 Wacker Neuson SE.

wackerneuson.com - 06.08.2015 Page: 3 / 3