



## AR 26

Concrete compaction in prefabricated concrete factories



### Quality exposed concrete surface is king: A case for the AR 26

First-class compacted concrete is essential for the production of concrete surfaces. Thanks to its high-quality design, Wacker Neuson's external vibrator AR 26 offers this precision compaction. The result: Beautifully smooth and level concrete surfaces on walls, pillars and columns.

- Long staying power thanks to its powerful electric motor with stable speeds.
- Available for all standard voltages and frequencies
- Fast assembly thanks to easy to use fastening clamps
- Ca. 2 kg lighter than its forerunner model AR 36.
- Small, compact and light.



Also available with a practical ON/OFF switch.



## Technical specifications

	<b>AR 26/6/042</b>	<b>AR 26/6/042 cs</b>	<b>AR 26/6/250</b>
Vibrations rpm	6,000	6,000	6,000
Centrifugal force max. kN	3.47	3.47	3.47
Rated voltage 3~ V	42	42	250
Rated current A	8	8	1.3
Weight kg	6.2	7.5	4.6
L x W x H mm	232 x 227 x 103		
Fastening	90 x 125	90 x 125	90 x 125

### **Please note**

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.  
Copyright © 2015 Wacker Neuson SE.