

KD 2x2

KD 2x2 Coldwater HighPressure Cleaner

- ▶ Mobile coldwater Unit for professional use
- ▶ Impact resistant rotation-moulded Chassis and Cover for long durability
- ▶ Triplex-Piston Pump with Brass Pump-Head, Ceramic-Plungers and st.st. Valves
- ▶ Multi-Functional Storage Facility for HP-Hose, electr. Cable and chemical intake Hose.
- ▶ Low pressure injector for Chemical Intake
- ▶ Multi-Storage Facility for Trigger-Gun, Spray-Wand and Rotary-Nozzle integrated in Chassis
- ▶ Water Break-Tank with 17 l capacity
- ▶ High-Pressure Chemical with Regulator-Valve
- ▶ Infinitely variable pressure control
- ▶ 2-fold safety system with overload protection
- ▶ **Standard equipment:** TSS-System: Total Start-Stop System with Off-Delay, Unit Total-Switch Off after 20 min, Leakage Recognition, Professional Hose-Reel with st.st. Shaft and 15m Hose, Watertank with 17l capacity, High-Pressure Detergent with Regulator-Valve, Rotary-Nozzle, High-Pressure Nozzle c/w. stainless steel Lance and Nozzle-Protection



Technical data	Unit	KD 623*	KD 823*	KD 940
Pressure	bar/ Mpa	30-150/ 3-15	30-130/ 3-13	30-190/ 3-19
Waterflow	l/min	10	12	14
Connected load	kW	2,5	3,1	4,0
Voltage	Ph/V/Hz	1/230/50	1/230/50	3/400/50
Temperature	C°	40	40	40
Nozzle size		25034 ■	2505 ■	25045 ■
HighPressure hose	m/NW [mm]	15/6	15/8	15/8
Engine speed	rpm	1400	1400	1400
Weight	kg	57	60	60
Part No.		558	562	561

*UK-Version may vary.