



HD Etronic II

Hotwater HighPressure Cleaner oil-heated

- ▶ Mobile hotwater Unit for professional use - oil-heated
- ▶ Metal-Chassis corrosion protected (fully zinc coated, iron phosphated, Powder coated) with impact resistant unit cover
- ▶ Security system consisting of pressure switch, unloader valve, safety valve, thermostat and overload protection
- ▶ Transparent Containers for visual level control

ETRONIC II - Features:

- ▶ TSS-System with Pump Off-Delay
- ▶ Burner-On Delay 2 seconds
- ▶ 24 V Safety-Circuit
- ▶ Leakage-Recognition
- ▶ Unit Total-Switch Off
- ▶ Hours-meter
- ▶ Low-Water Cut-Off
- ▶ Low-Fuel Cut-Off
- ▶ Flame-Monitor with Photocell
- ▶ Steam-Stage
- ▶ 2-Stage Switch Pump-Burner On/Off
- ▶ Horizontal Heatexchanger
- ▶ Flame - Failure Lamp
- ▶ Option: Hose Reel up to max. 40 m HP-Hose possible



* Unit shows options

- ▶ **Standard equipment:** 10m H.P.Hose, Trigger-Gun Power 315 ST, stainless steel Lance 900mm, Nozzle-Protection and stainless steel High-Pressure Nozzle and Nozzle Protection

Technical data	Unit	HD 723*	HD 840	HD 940	HD 1140	HD 1240
Pressure	bar/ Mpa	30-120/ 3-12	30-160/ 3-16	30-180/ 3-18/	30-230/ 23	30-165/ 3-16,5
Waterflow	l/min	12	12	14	16	20
Connected load	kW	3,6	4,4	5,0	7,9	7,9
Voltage	Ph/V/Hz	1/230/50	3/400/50	3/400/50	3/400/50	3/400/50
Temperature	C°	30-150	30-150	30-150	30-150	30-150
Nozzle size		25045 ■	2507 ■			
HighPressure hose	m/NW [mm]	10/8	10/8	10/8	10/8	10/8
Engine speed	rpm	1400	1400	1400	1400	1400
Weight	kg	150	150	150	155	160
Part No.		496	408	442	410	411

*13A-UK-Version: 330-720 l/h, 30-110 bar