



Art. no. **4400**
Art. no. **4400/4**

Lever action grease gun, suitable for the use with bulk grease or with grease cartridges. With steel braid outlet hose \varnothing ext. 10 mm x 300 mm length, M 10x1, and 4 – jaws – hydraulic coupler. Suitable for grease up to a viscosity of NLGI 2.

Art. no.	Max delivery	Max outlet pressure	Capacity grease cartridge	\varnothing suitable grease cartridge	L. suitable grease cartridge	Weight	Dimensions (LxWxH) (mm)
4400	1,2 g/stroke	400 bar	600 g	56 mm	500 mm	1,70 kg	150x480x60
4400/4	1,2 g/stroke	400 bar	400 g	54 mm	500 mm	1,70 kg	150x480x60



Art. no. **4450**
Art. no. **4450/4**

Pneumatic grease gun, suitable for the use with bulk grease or with grease cartridges. With steel braid outlet hose \varnothing ext. 10 mm x 300 mm length, M 10x1, and 4 – jaws – hydraulic coupler. It is a single action mechanism (non-continuous grease supply): when activating the trigger, the internal piston moves and supplies grease; when the trigger is released, the piston returns in its initial position. By repeating this procedure the grease can be dispensed. Compressed air pressure: 4 – 8 bar. Suitable for grease up to a viscosity of NLGI 2.

Art. no.	Max delivery	Max outlet pressure	Capacity grease cartridge	\varnothing suitable grease cartridge	L. suitable grease cartridge	Weight	Dimensions (LxWxH) (mm)
4450	1,2 g/stroke	300 bar	600 g	56 mm	500 mm	2 kg	240x440x70
4450/4	1,2 g/stroke	300 bar	400 g	54 mm	500 mm	2 kg	240x440x70



Art. no. **4452**
Art. no. **4452/4**

Electric grease gun with 12 V - battery, suitable for the use with bulk grease or with grease cartridges. With steel braid outlet hose \varnothing ext. 10 mm x 300 mm length, M 10x1, and 4 – jaws – hydraulic coupler. The grease is dispensed continuously; by pushing the trigger of the grease gun, the internal gears start moving and the grease is supplied. When the trigger is released again, the grease flow stops. Battery charger: 12 VDC (1300 mAh), time for recharging: 1 hour (according to the ROHS – directive). Battery recharger: 230 Vac (12 V DC, 50 Hz). Supplied in a plastic case with a lever grease gun head for the use as lever grease gun. Suitable for grease up to a viscosity of NLGI 2.

Art. no.	Max delivery	Max outlet pressure	Capacity grease cartridge	\varnothing suitable grease cartridge	L. suitable grease cartridge	Weight	Dimensions (LxWxH) (mm)
4452	8 g/stroke	300 bar	600 g	56 mm	500 mm	7,5 kg	540x430x110
4452/4	8 g/stroke	300 bar	400 g	54 mm	500 mm	7,5 kg	540x430x110



Art. no. **4405**

Cartridge with lithium grease, NLGI 2, with 600 g capacity. Diameter 56 mm, length 300 mm. Kinematic viscosity of the basing oil: 150 cSt, 40°C. Temperature range of use: -20°C - +120°C. According DIN 51502 K 2 K-20. Packaging unit: 15 pcs.

Art. no. **4406**

Cartridge with lithium grease, NLGI 2, with 400 g capacity. Diameter 52 mm, length 235 mm. Kinematic viscosity of the basing oil: 150 cSt, 40°C. Temperature range of use: -20°C - +120°C. According DIN 1284. Packaging unit: 15 pcs.