



Art. no. **6728**

Art. no. **6728**

Automatic shut-off dispensing nozzle for petrol, with rubber protection, connection 3/4" BSP (F).
Max flow rate 50 l/min.



Art. no. **6702/B**

Art. no. **6702/B**

Manual dispensing nozzle for petrol, body in aluminium with plastic handle protector, with inlet swivel 1" BSP (M-F) and dispensing outlet with ø ext. 25 mm, with latch for locking of trigger.
Max flow rate 150 l/min.



Art. no. **2867**

Art. no. **2867**

Mechanical nutating – disk flow meter for petrol, kerosene and diesel, with 3 – digits partial meter (max. 999 l; resettable to zero) and 6 – digits totalizer (non resettable). The meter can easily be calibrated and it can also be used for gravity applications. The upper part can be rotated so that 4 different flow directions are possible. The flow meter is constructed in accordance with directive ATEX 99/92/EC – IECEx (group II – category 2 – G IIB T6) and so is suitable also for the use in environments with a high explosion risk.



Art. no.	Flow range	Max working pressure	Burst pressure	Accuracy*	Resolution	Connection threads	Weight
2867	20 – 120 l/min	3,5 bar	28 bar	+/- 1%	0,01 l	1" BSP (F)	0,6 kg

* Accuracy in % of flow range after calibration



Art. no. **2869**

Art. no. **2869**

Electronic oscillating - disk flow meter for petrol, body in aluminium, with 6 – digits partial meter (resettable to zero) and 6 – digits totalizer (non resettable). The meter includes also a flow rate indicator. The upper part can be rotated so that 4 different flow directions are possible.

Art. no.	Flow range	Max working pressure	Burst pressure	Accuracy*	Resolution	Connection threads	Weight
2869	5 – 120 l/min	3,5 bar	28 bar	+/- 0,5%	0,01 l	1" BSP (F)	1,1 kg

* Accuracy in % of flow range after calibration