



Art. no. **6435**

Art. no. **6435**

Electric vane pump, selfpriming, 230 VAC, for the transfer of diesel. Rotor in sintered steel and vanes in acetal resin. The pump has a built-in bypass valve; protection category IP 55. Delivery 60 l/min.

**60 l/min**

Art. no.	Voltage	Power	Current drain	Rpm	Delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
<b>6435</b>	230 VAC	370 W	1,5 A	2800	60 l/min	1" BSP (F)	7 kg	170x190x230



Art. no. **6218**  
Art. no. **6219**

Art. no. **6218**  
Art. no. **6219**

Electric vane pump, selfpriming, 230 VAC or 400 VAC, for the transfer of diesel. Rotor in sintered steel and vanes in acetal resin. The pump has a built-in bypass valve; protection category IP 55. The low number of rotations of the motor permits a constant flow without turbulences, a low noise and less abrasion of the components. Delivery 60 l/min. at 900 rpm.

**65 l/min**

Art. no.	Voltage	Power	Current drain	Rpm	Delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
<b>6218</b>	400 VAC	550 W	2,5 A	900	65 l/min	1" BSP (F)	15 kg	200x240x300
<b>6219</b>	230 VAC	700 W	6,2 A	900	65 l/min	1" BSP (F)	15 kg	200x240x300



Art. no. **6220**

Art. no. **6220**

Electric vane pump, selfpriming, 230 VAC, for the transfer of diesel. Rotor in sintered steel and vanes in acetal resin. The pump has a built-in bypass valve; protection category IP 55. Delivery 100 l/min. at 1420 rpm.

**100 l/min**

Art. no.	Voltage	Power	Current drain	Rpm	Delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
<b>6220</b>	230 VAC	550 W	6,2 A	1420	100 l/min	1" BSP (F)	15 Kg	200x240x300

