# **WASTE OIL DRAINERS**





Art. no. **3185** Art. no. **3185/110** 

Mobile low level gravity waste oil drainer, suitable for the draining of motor oil, gear oil or differential oil from trucks and passenger cars.

Available with collection capacity of 70 l and 110 l, with anti splash grid and removable, lateral antisplash guard (optional). The unit can be discharged by gravity through the laterally mounted 3/4" drain valve or by using an evacuation pump with suction hose and female quick coupling to be connected to the male coupling installed on the drainer (see evacuation kit art. no. 2044 + 2264 on page 123!).





#### Art. no. 3185/20

Mobile low level gravity waste oil drainer such as above, but in height-reduced version, ideal for the use with passenger cars with sports chassis.

| Art. no. | Collection capacity | Connections  | Weight | Dimensions<br>(LxWxH) (mm) |
|----------|---------------------|--------------|--------|----------------------------|
| 3185     | 70 l                | 3/4" BSP (F) | 26 Kg  | 800x560x180                |
| 3185/110 | 110                 | 3/4" BSP (F) | 38 Kg  | 1400x560x180               |
| 3185/20  | 22 l                | 3/4" BSP (F) | 18 Kg  | 800x500x80                 |





## Art. no. **3186** Art. no. **3186/110**

Pit gravity waste oil drainer, suitable for the draining of motor oil, gear oil or differential oil from trucks and passenger cars. Available with collection capacity of 70 l and 110 l, with anti splash grid and metal rollers. Suitable for the use in service pits between the pit rails. It is possible to adapt the width according to the pit dimensions. The unit can be discharged by gravity through the laterally mounted 3/4" drain valve or by using an evacuation pump with suction hose and female quick coupling to be connected to the male coupling installed on the drainer (see evacuation kit art. no. 2044 + 2264 on page 123!).



| Art. no. | Collection capacity | Width adjustment range (mm) | Connections  | Weight | Dimensions<br>(LxWxH) (mm) |
|----------|---------------------|-----------------------------|--------------|--------|----------------------------|
| 3186     | 70 l                | Min 900 - Max 1300          | 3/4" BSP (F) | 27 Kg  | 800x560x180                |
| 3186/110 | 110 l               | Min 900 - Max 1300          | 3/4" BSP (F) | 39 Kg  | 800x560x285                |





Art. no. **3254** Art. no. **3254/110** 

Mobile low level gravity drainer, suitable for the draining of waste oils and antifreeze from trucks and passenger cars by using the included pump kit for the eventual refilling of the liquid into the motor or circuit after finishing the service.

Available with collection capacity of 70 I and 110 I, with anti splash grid.

The pump kit consists of a pneumatic 1,3:1 – pump, pressure regulator with manometer, suction hose and supply hose gun with rigid outlet pipe.



| Art. no. | Compressed air supply | Outlet<br>pressure | Delivery | Collection capacity | Connections | Weight | Dimensions<br>(LxWxH) (mm) |
|----------|-----------------------|--------------------|----------|---------------------|-------------|--------|----------------------------|
| 3254     | 2-4 bar               | 4 bar              | 10 l/min | 70 I                | 1/2"BSP (F) | 34 Kg  | 800x560x180                |
| 3254/110 | 2-4 bar               | 4 bar              | 10 l/min | 1101                | 1/2"BSP (F) | 46 Kg  | 800x560x285                |



# **WASTE OIL DRAINERS**





#### Art. no. 3292

Waste oil draining kit for the installation in service pits, with metal collection bowl of 10 l capacity incl. removable anti splash grid and height-adjustable, telescopic tube with wall mounted swivel arm in galvanized steel.

#### Art. no. 3244

Waste oil draining kit for the installation in service pits, with metal collection bowl of 10 l capacity incl. removable anti splash grid, height-adjustable, telescopic tube with wall mounted swivel arm in galvanized steel and pneumatic 1:1 – pump, art. no. 2044, for the discharge of the collected waste oil and the transfer into a waste oil storage tank.


| Y H                  |  |
|----------------------|--|
|                      |  |
|                      |  |
| Art. no. <b>3244</b> |  |

| Art.<br>no. | Diameter<br>collection<br>bowl | Capacity<br>collection<br>bowl | Max extension<br>height<br>collection bowl | Max extension<br>length swivel arm | Connections | Weight |
|-------------|--------------------------------|--------------------------------|--|------------------------------------|-------------|--------|
| 3292        | 400 mm                         | 10 l                           | 530 mm                                     | 1340 mm                            | 1" BSP (F)  | 10 Kg  |
| 3244        | 400 mm                         | 10 l                           | 530 mm                                     | 1340 mm                            | 1" BSP (F)  | 20 Kg  |



#### Art. no. 3293

Waste oil draining kit for the installation in service pits, with metal, trapezoidal collection bowl of 30 l capacity incl. removable anti splash grid and height-adjustable, telescopic tube with wall mounted swivel arm in galvanized steel.



| Art. no. | Dimensions<br>collection bowl<br>(LxWxH) (mm) | Capacity collection bowl | Max extension<br>height<br>collection bowl | Max extension<br>length swivel<br>arm | Connections | Weight |
|----------|---|--------------------------|--|---------------------------------------|-------------|--------|
| 3293     | 395x350x360 mm                                | 301                      | 530 mm                                     | 1340 mm                               | 1"BSP (F)   | 15 Kg  |



### Art. no. 2046 - Art. no. 2044

Waste oil evacuation and transfer kit, consisting of a 1:1 – (art. no. 2044) or a 2:1 – (art. no. 2046) single acting pneumatic piston pump, wall bracket, 1,5 m - rubber suction hose Ø 1" and foot valve with stainless steel strainer.

#### Art. no. 2043

Pneumatic 1:1 – single acting piston pump, suitable for the evacuation and the transfer of waste oil. Delivery approx. 35 l/min.

#### Art. no. 2264

Waste oil and waste antifreeze evacuation kit, consisting of hydraulic quick coupling with connection 1" BSP (F), hydraulic quick connector with connection 1" BSP (F) and connection adapter with connection 1" BSP (MM), with non-return valve. The kit is necessary to carry out the evacuation of waste oil drainers or waste oil suction units by connecting the hydraulic quick coupling to the suction hose of evacuation kits art. no. 2046 or art. no. 2044 (instead of the installed foot valve) and the quick connector to the waste oil drainer or waste oil suction unit to be discharged.

## Art. no. 2045

Pneumatic 2:1 – single acting piston pump, with Viton® - gaskets, suction tube in brass, and foot valve in stainless steel, suitable for the evacuation and the transfer of waste oil and waste antifreeze. Delivery approx. 35 l/min.

| Art.<br>no. | Compressed air supply | Delivery | Compression ratio | Max outlet pressure | Connection compressed air |             | Consumption compressed air | Weight |
|-------------|-----------------------|----------|-------------------|---------------------|---------------------------|-------------|----------------------------|--------|
| 2046        | 2 – 8 bar             | 30 l/min | 2:1               | 16 bar              | 1/4"BSP (F)               | 3/4"BSP (M) | 240 l/min                  | 5 kg   |
| 2044        | 2 – 8 bar             | 35 l/min | 1:1               | 8 bar               | 1/4"BSP (F)               | 3/4"BSP (M) | 210 l/min                  | 4 kg   |
| 2043        | 2 – 8 bar             | 35 l/min | 1:1               | 8 bar               | 1/4"BSP (F)               | 3/4"BSP (M) | 210 l/min                  | 4 kg   |
| 2045        | 2 – 8 bar             | 35 l/min | 2:1               | 16 bar              | 1/4"BSP (F)               | 3/4"BSP (M) | 240 l/min                  | 5 kg   |



Mobile waste oil gravity drainers, with metal collection bowl and height-adjustable, telescopic tube. The collection of the waste oil is made by using empty jerrycans or drums.



## Art. no. 3177

Mobile waste oil gravity drainer, consisting of wide collection bowl in painted steel of 10 l capacity, art. no. 3290, incl. removable anti splash grid, height-adjustable, telescopic tube with 2"x 28 mm – bung adapter, shut-off valve and trolley for max. 60 l – drums, art. no. 4360.

#### **OPTIONAL:**

- metal crown drain adapter, permits to enlarge the collection diameter of the drain bowl (= art. no. 3299).
- empty plastic can, capacity 20 l (= art. no. 3482).



| Art. no. | Capacity<br>collection<br>bowl | Height<br>adjustable<br>up to | Ø collection<br>bowl art. no.<br>3290 | Ø metal crown<br>drain adapter art.<br>no. 3299 | Weight | Dimensions<br>(LxWxH) (mm) |
|----------|--------------------------------|-------------------------------|---------------------------------------|---|--------|----------------------------|
| 3177     | 10 l                           | 1600 mm                       | 400 mm                                | 590 mm  | 18 kg  | 700 x 700 x 1200           |





# Art. no. 3178

Mobile waste oil gravity drainer, consisting of wide collection bowl in painted steel of 10 I capacity, art. no. 3290, incl. removable anti splash grid, height-adjustable, telescopic tube with 2" x 28 mm - bung adapter, shut-off valve and trolley for max. 208 I – drums, art. no. 4380.

#### OPTIONAL:

- metal crown drain adapter, permits to enlarge the collection diameter of the drain bowl (= art. no. 3299);
- mechanical level gauge with floater and analogical measuring scale, suitable for 208 l drums (= art. no. 8752);
- empty metal drum, capacity 208 l (= art. no. 4699).



| Art. no. | collection adjustable bowl art. no. drain a |         | Ø metal crown<br>drain adapter<br>art. no. 3299 | Weight | Dimensions<br>(LxWxH) (mm) |                  |
|----------|---|---------|---|--------|----------------------------|------------------|
| 3178     | 101   | 1800 mm | 400 mm  | 590 mm | 31 kg                      | 700 x 700 x 1200 |



Waste oil Pag. 124



Mobile waste oil gravity drainers, with metal collection bowl and height-adjustable, telescopic tube. The collection of the waste oil is made by using empty jerrycans or drums.



#### Art. no. 3173

Mobile waste oil gravity drainer, consisting of wide collection bowl in painted steel of 10 l capacity, art. no. 3290, incl. removable anti splash grid, height-adjustable, telescopic tube with 2" x 28 mm – bung adapter, shut-off valve and heavy duty trolley for max. 208 l – drums, art. no. 4389.

#### **OPTIONAL:**

- metal crown drain adapter, permits to enlarge the collection diameter of the drain bowl (= art. no. 3299);
- mechanical level gauge with floater and analogical measuring scale, suitable for 208 I – drums (= art. no. 8752);
- empty metal drum, capacity 208 I (= art. no. 4699).



| Art. no. |      |         | Ø collection<br>bowl art. no.<br>3290 | Ø metal crown<br>drain adapter art.<br>no. 3299 | Weight | Dimensions<br>(LxWxH) (mm) |
|----------|------|---------|---------------------------------------|---|--------|----------------------------|
| 3173     | 10 l | 1800 mm | 400 mm                                | 590 mm  | 44 kg  | 700 x 700 x 1200           |





# Art. no. 3183

Mobile waste oil gravity drainer, suitable especially for the waste oil collection from motorbikes. Consisting of wide, rectangular collection bowl (dimensions 700 x 250 mm) of 80 mm height incl. removable anti splash grid, assuring an easy access between lift and motorbike, collection container of 65 l capacity, level gauge, two fixed wheels and two castors. The unit can be discharged pneumatically by connecting it to compressed air through a discharge hose with curved outlet tube.



| Art. no. | Capacity collection bowl | Height<br>adjustable<br>up to | Capacity collection container | Max<br>collection<br>quantity | Discharge<br>pressure | Weight | Dimensions<br>(LxWxH) (mm) |
|----------|--------------------------|-------------------------------|-------------------------------|-------------------------------|-----------------------|--------|----------------------------|
| 3183     | 101                      | 1400 mm                       | 65 l                          | 501                           | 0,5 bar               | 30 Kg  | 430x570x1200               |

# **WASTE OIL DRAINERS**



Waste oil gravity drainer, with metal collection bowl and height-adjustable, telescopic tube that can be extended until a height of max. 1,6 m. The unit can be discharged pneumatically by connecting it to compressed air through a discharge hose with curved outlet tube. The discharge alternatively can also be made by using a pneumatic waste oil discharge pump art. no. 2044 (see on page 123!) that is connected to the discharge valve of the container or with a wall-mounted waste oil discharge kit which can transfer the sucked oil into a waste oil storage tank.



## Art. no. 3179

Mobile waste oil gravity drainer, suitable for the use under lifts, with collection container of 90 I capacity, level gauge, two fixed wheels and two castors, with wide collection bowl in painted steel of 10 I capacity incl. removable anti splash grid, 1,6 m discharge hose.

#### **OPTIONAL:**

- metal crown drain adapter, permits to enlarge the collection diameter of the drain bowl (= art. no. 3299).



| Art. no. | Capacity collection bowl |              | Capacity collection container | Max.<br>collection<br>quantity | Discharge<br>pressure | Weight | Dimensions<br>(LxWxH) (mm) |
|----------|--------------------------|--------------|-------------------------------|--------------------------------|-----------------------|--------|----------------------------|
| 3179     | 101                      | 1050-1600 mm | 90 l                          | 801                            | 0,5 bar               | 28 Kg  | 504x460x1200               |





# Art. no. 3161

Mobile waste oil gravity drainer, suitable for the use under lifts, with collection container of 60 l capacity, level gauge, two fixed wheels and two castors, with wide collection bowl in painted steel of 10 l capacity incl. removable anti splash grid, 1,6 m discharge hose.

# **OPTIONAL:**

- metal crown drain adapter, permits to enlarge the collection diameter of the drain bowl (= art. no. 3299).



| Art. no. | Capacity collection bowl |              | Capacity collection container | Max<br>collection<br>quantity | Discharge<br>pressure | Weight | Dimensions<br>(LxWxH) (mm) |
|----------|--------------------------|--------------|-------------------------------|-------------------------------|-----------------------|--------|----------------------------|
| 3161     | 10 l                     | 1000-1500 mm | 60 I                          | 50 I                          | 0,5 bar               | 26 Kg  | 504x460x1100               |



Waste oil Pag. 126



Waste oil gravity drainer, with metal collection bowl and height-adjustable, telescopic tube that can be extended until a height of max. 1600 / 1800 mm.



## Art. no. **3191**

Mobile waste oil gravity drainer, suitable for the use under lifts or in pits, with collection container of 90 I capacity, two fixed wheels and two castors, with wide collection bowl in painted steel of 10 I capacity incl. removable anti splash grid, level gauge and storage bowl. The unit can be discharged with a pneumatic 1:1 – pump (art. no. 2043), mounted on top of the container, through the included 1,6 m discharge hose.

## **OPTIONAL:**

-- metal crown drain adapter, permits to enlarge the collection diameter of the drain bowl (= art. no. 3299).

| Art. no. | Capacity collection bowl |              | Capacity collection container | Max<br>collection<br>quantity | Discharge<br>pressure | Weight | Dimensions<br>(LxWxH) (mm) | W   |
|----------|--------------------------|--------------|-------------------------------|-------------------------------|-----------------------|--------|----------------------------|-----|
| 3191     | 10                       | 1050-1600 mm | 901                           | 801                           | 0,5 bar               | 35 Kg  | 504x460x1200               | Nr. |





# Art. no. 3193

Mobile waste oil gravity drainer, suitable for the use under lifts or in pits, with collection container of 110 I capacity, two fixed wheels and two castors, with wide collection bowl in painted steel of 10 I capacity incl. removable anti splash grid, level gauge and storage bowl. The unit can be discharged with a pneumatic 1:1 – pump (art. no. 2043), mounted on top of the container, through the included 1,6 m discharge hose.

### **OPTIONAL:**

-- metal crown drain adapter, permits to enlarge the collection diameter of the drain bowl (= art. no. 3299).

| I | Art. no. | Capacity collection bowl | Height<br>adjustable | Capacity collection container | Max<br>collection<br>quantity | Discharge<br>pressure | Weight | Dimensions<br>(LxWxH) (mm) |
|---|----------|--------------------------|----------------------|-------------------------------|-------------------------------|-----------------------|--------|----------------------------|
|   | 3193     | 10 l                     | 1200-1800 mm         | 1101                          | 100 l                         | 0,5 bar               | 37 Kg  | 510x470x1300               |

Waste oil Pag. 127