

## “MP” Heavy Duty Transparent Hose



1

### Properties

- Excellent in high pressure
- Light weight visible material flow
- Smooth bore, exposed PVC helix
- Series T13 provides anti-static with copper wire inserted

### Applications

- Heavy duty suction / discharge
- Fish suction / discharge
- Underwater pump, High slope suction
- Transfer clay, condensed liquids, sludge
- Suction hose for dump truck

### Temperature Range

-50 °F to 150 °F

Size (inch)	I.D. (mm)	O.D. (mm)	Length (m)	Pressure at 20°C (kg/m <sup>2</sup> )		Weight/Meter (+/-5%)
				Working	Bursting	
2"	50.0 +/-1.0	62.4 +/-1.5	50	9	18	0.88 kg
2-1/2"	65.0 +/-1.0	76.5 +/-1.5	50	9	18	1.10 kg
3"	75.0 +/-1.0	91.4 +/-1.5	50	9	18	1.53 kg
4"	100.0 +/-1.5	119.9 +/-2.0	30	9	18	2.48 kg
6"	150.0 +/-1.5	182.1 +/-2.0	20	9	16	5.55 kg

For further information, please feel free to contact Mr,Johnson Kwan on 9236 3957 or Mr Jack Chiu on 6427 5665, thx!