



“JK” 手提/移動式通風機

“JK” Portable/Mobile Axial Flow Fan



Product Features:

1. Energy saving and environmental protection
2. A Strong Wind
3. Using aluminum alloy die-casting, low noise, light weight
4. Reasonable structure, strong suction, good ability

1

Portable 手提式									
Model	Inch	Dia. (mm)	Volt. (V)	Frequency (Hz)	Power (Kw)	Speed (r/min)	Volume (m3/h)	Static Pre. (Pa)	Noise (dB(A))
BL08-110V-P	8"	200	110/220V	50/60	0.15	2900	1500	200	61
BL10-110V-P	10"	250	110/220V	50/60	0.35	2900	2700	250	66
BL12-110V-P	12"	300	110/220V	50/60	0.55	2900	3720	300	69
BL14-110V-P	14"	350	110/220V	50/60	0.7	2900	5100	350	76
BL16-110V-P	16"	400	110/220/380V	50/60	1.5	1450	5880	149	79
BL18-110V-P	18"	450	110/220/380V	50/60	5.5	1450	8040	160	71
BL20-110V-P	20"	500	110/220/380V	50/60	7.5	1450	9960	170	73

Product Application:

1. Especially for large playground, farms, open hall
2. In hull welding, can cover, build a bridge when the blow to the emission of harmful gases
3. For fire exhaust, pipeline construction and other harsh working environment needs for ventilation.



Mobile 移動式									
Model	Inch	Dia. (mm)	Volt. (V)	Frequency (Hz)	Power (Kw)	Speed (r/min)	Volume (m3/h)	Static Pre. (Pa)	Noise (dB(A))
BL16-110V-M	16"	400	110/220/380V	50/60	0.55	1450	5880	149	68
BL16-110V-M1	16"	400	110/220/380V	50/60	1.5	2900	7680	350	79
BL20-110V-M	20"	500	110/220/380V	50/60	0.75	1450	9960	170	73
BL24-380V-M	24"	600	220/380V	50/60	2.2	1450	17400	280	79
BL28-380V-M	28"	700	380V	50	3	1450	21000	350	79
BL32-380V-M	32"	800	380V	50	4	1450	22800	380	80



“JK” 低噪音軸流通風機

“JK” Low Noise Axial Flow Fan

Celler 地下室




Weld 燒焊



Tunnel 隧道



1

Cylinder 圓筒式Stationary 固定式High Mount 崗位式

110V/220V

Model	Inch	Dia. (mm)	Type	Volt. (V)	Power (Kw)	Speed (r/min)	Volume (m3/h)	Static Pre. (Pa)	Noise (dB(A))
BL08-110V-C	8"	200	C/S	110/220V	0.06	1450	600	20	57
BL08-110V-C1	8"	200	C/S	110/220V	0.12	2800	1300	140	62
BL10-110V-C	10"	250	C/S	110/220V	0.09	1450	1000	35	59
BL10-110V-C1	10"	250	C/S	110/220V	0.25	2800	2100	215	65
BL12-110V-C	12"	300	C/S/H	110/220V	0.15	1450	2000	59	61
BL12-110V-C1	12"	300	C/S/H	110/220V	0.37	2800	3000	230	68
BL16-110V-C	16"	400	C/S/H	110/220V	0.55	1450	5300	167	72
BL16-110V-C1	16"	400	C/S/H	110/220V	1.5	2800	11000	320	75
BL20-110V-C	20"	500	C/S/H	110/220V	0.75	1450	9300	200	74

380V

Model	Inch	Dia. (mm)	Type	Volt. (V)	Power (Kw)	Speed (r/min)	Volume (m3/h)	Static Pre. (Pa)	Noise (dB(A))
BL24-380V-C	24"	600	C/S/H	380V	2.2	1450	18700	300	80
BL28-380V-C	28"	700	C/S	380V	3	1450	21500	210	85
BL28-380V-C1	28"	700	C/S	380V	2.2	1450	24500	350	85
BL32-380V-C	32"	800	C/S	380V	4	1450	28000	380	88
BL40-380V-C	40"	1000	C/S	380V	4	960	50000	260	88
BL48-380V-C	48"	1200	C/S	380V	4	720	58000	280	90