

for Flammables

## Outdoor Safety Lockers—Non-Combustible **NEW**

Safe, secure storage for flammables and hazardous chemicals

- Leakproof, all welded sump with galvanized steel grate flooring.
- 42-in (1.07-m) wide steel door system with 3-point lock.
- Chemical and UV resistant coating, inside and out.


Protect people and the environment and meet insurance requirements by storing hazardous materials in rugged, FM-approved Outdoor Safety Lockers. Non-combustible construction with heavy gauge steel and built-in secondary containment, every locker is fully compliant to meet EPA 40 CFR, NFPA 30 and NFPA 1 regulations. Proper chemical storage reduces poison hazards and accidents, minimizes contamination of chemicals, and prevents unwanted, costly fines.

Each locker features natural draft ventilation, NFPA 704 diamond decal for content identification, anchoring plates for hold down protection, and multiple static grounding connections for maximum safety. Forklift channels permit easy relocation.


Choose explosion relief panels for the storage of highly volatile Class 1A or dispensing of Class 1 A and 1B flammables as defined by NFPA – always check with the local authority having jurisdiction to ensure safety by following all local regulations, including proper setback requirements.



Sixteen-drum locker with optional steel ramp simplifies drum loading.



1. Air vents on both sides
2. Inside grounding lug
3. Leakproof sump with removable, galvanized steel grate floor
4. High visibility safety strip
5. Forklift channels
6. 3-point latching system
7. Outside grounding lug and anchor plate
8. Explosion relief design with blow-out panels



For added convenience and safety . . . Include ramp, shelving, grounding kit, fire protection and more – see page 62 for optional accessories.

**NON-COMBUSTIBLE** OUTDOOR SAFETY LOCKERS



55-Gal Drum Capacity	Sump Capacity Gallons/Liters	Dimensions W x D x H		Approval/Lstg Regulation	Standard		Explosion Relief	
		Exterior*	Interior		Model No	Ship Wt lb/kg	Model No	Ship Wt lb/kg
2	120/454	67 in x 38 in x 75 in 1702 mm x 965 mm x 1905 mm	54 in x 30 in x 55.5 in 1372 mm x 762 mm x 1410 mm	FM,N,A,E	911020	982/445	911021	1069/485
4	100/379	67 in x 62 in x 75 in 1702 mm x 1575 mm x 1905 mm	54 in x 54 in x 62 in 1372 mm x 1372 mm x 1575 mm		911040	1341/608	911041	1428/648
6	140/530	91 in x 62 in x 97 in 2311 mm x 1575 mm x 2464 mm	78 in x 54 in x 84 in 1981 mm x 1372 mm x 2134 mm		911060	1658/752	911061	1745/792
9	198/750	91 in x 86 in x 97 in 2311 mm x 2184 mm x 2464 mm	78 in x 78 in x 84 in 1981 mm x 1981 mm x 2134 mm		911090	2101/953	911091	2203/999
12	253/958	84 in x 115 in x 97 in 2134 mm x 2921 mm x 2464 mm	78 in x 102 in x 84 in 1981 mm x 2591 mm x 2134 mm		911120	2442/1108	911121	2616/1187
16	326/1234	115 in x 110 in x 97 in 2921 mm x 2794 mm x 2464 mm	102 in x 102 in x 84 in 2591 mm x 2591 mm x 2134 mm		911160	2959/1342	911161	3126/1418

Note: Door height on 2- and 4-drum models is 51-in (1.30-m) high and 80-in (2.03-m) high on 6- through 16-drum models. \*Dimensions include mounting plates and door hardware. In most instances, locker sizes 2- through 6-drum are available to ship via a closed container truck, which can potentially reduce freight costs as compared to flat bed shipping alternatives.

# OUTDOOR SAFETY LOCKERS

## Accessories for Outdoor Lockers

### Outdoor Safety Lockers – Optional Accessories **NEW**

Accessorize your non-combustible locker with options that improve function and add convenience

Customize your locker to meet specific applications with a variety of optional features and accessories designed to meet code and increase safety.


- Add sturdy steel ramps to simplify loading or unloading heavy drums with a drum dolly.
- Add galvanized steel shelving for organized, easy access to smaller containers.
- Add fiberglass grate flooring with poly sump liner for greater resistance against corrosive chemical spills.



#### Loading Ramp

Steel with anti-skid yellow paint

- **Model 915001:**  
48-in (1219-mm) W x 120-in (3048-mm) L
- **Model 915003:**  
48-in (1219-mm) W x 88-in (2235-mm) L




#### Grounding Kit Model 915505

Kit comes with rod – 5/8-in (16-mm) diameter x 8-ft (2438-mm) L, wire and connector



#### Fiberglass Grate with Sump Liner Models 915201 - 915211

High density polyethylene (HDPE) sump liner and fiberglass grate flooring for acid and corrosive chemical spill resistance



#### Shelving Models 915101 - 915105

Galvanized steel shelving. Two-tier, 16-in (406-mm) wide with mounting brackets—back wall only

Not available on locker models with explosion relief panels. Shelf package for 2- and 4-drum models (915101) will limit the ability to load locker to full drum capacity.



#### Basic Fire Protection System

Models 915401 Model 915403

BC Type, FE-227 extinguisher unit, ceiling mounted and fuse linked

Locker Capacity	Grounding Kit		Loading Ramp		Galvanized Steel* Shelving - 2 Tier		Fiberglass† Grate Flooring (with Sump Liner)		Basic Fire† Protection System			
	Model No	Weight lb/kg	Model No	Weight lb/kg	Model No	Weight lb/kg	Model No	Weight lb/kg	Model No	Weight lb/kg		
2-drum	915505	10/5	915001	300/136	915101	69/29	—	—	915401	12/5		
4-drum												
6-drum			915003	225/102	915103	86/39			915201	915203	915403	35/16
9-drum												
12-drum												
16-drum												

† These accessories must be purchased in conjunction with a locker to ensure proper installation and to retain FM approval.

\* Shelving is not available on models with explosion relief panels. Shelf package for 2- and 4-drum models (915101) will limit the ability to load locker to full capacity.

Justrite's full line of Outdoor Safety Lockers—visit our website for details.

**NON-COMBUSTIBLE**  
OUTDOOR SAFETY LOCKERS

**AGRI-TURF™**  
OUTDOOR SAFETY LOCKERS

**2 HOUR FIRE-RATED**  
OUTDOOR SAFETY LOCKERS

**4 HOUR FIRE-RATED**  
OUTDOOR SAFETY LOCKERS

