ST 氣動式油壓千斤頂

- 碳鋼底座，自動化焊接，品質穩定。
- 合金鋼主軸高強度、耐荷重，表面硬鉻處理，質輕、易攜帶，具自動回縮功能。
- 各型號均附墊塊組、採用空氣動力泵浦、上昇速度快，讓工作效率更高。

Hydraulic Bottle Jack with Air Pump

※Carbon steel base with automatic welding makes stable quality.
※Chrome plated plunger with self-return resists corrosion and extends life.
※Fast motion by air pump design makes heigh efficiency.
※Saddle set are included on all models.

ST-series

STA-50

Model Number 型 號	Capacity 能 力 (ton)	Stroke 揚 程 (mm)	Min. Height 本身高 A (mm)	Ext. Height 伸長總高 B (mm)	Plunger Diam. 主軸直徑 J (mm)	Base Dimensions 底座尺寸 L x W (mm)	Auxiliary Height 輔助高 (mm)	Air pressure range 使用空壓 (kgf/cm^2)	Weight 總 重 (kg)
ST-20H	20	344	455	799	50	128 x 181	10,45,80,160	8-12	22.0
ST-20A		150	235	385	50	128 x 181	10,45,80	8-12	16.0
ST-20B		125	210	335	50	128 x 181	10,45,80	8-12	15.0
ST-20C		100	185	285	50	128 x 181	10,45,80	8-12	14.0
ST-30A	30	145	235	380	60	141 x 197	10,45,80	8-12	22.0
ST-30B		120	210	330	60	141 x 197	10,45,80	8-12	21.0
STA-50	50	150	248	398	70	150 x 170	10,45,80	8-12	37.0

STH 手動/ 氣動二用型千斤頂

- 碳鋼底座，自動化焊接，品質穩定。
- 合金鋼主軸高強度，耐荷重，表面硬鉻處理，質輕、易攜帶，具自動回縮功能。
- 採空氣動力泵浦，上昇速度快，工作效率高。
- 各型號均附墊塊組。

Dual purpose Jack, Manual/ Pneumatic

※Carbon steel base with automatic welding makes stable quality.
※Chrome plated plunger with self-return. resists corrosion and extends life.
※Fast motion by air pump design makes high efficiency.
※Saddle set are included on all models.

STH-20A

Model Number 型號	Capacity 能力 (ton)	Stroke 揚程 (mm)	Min. Height 本身高 A (mm)	Ext. Height 伸長總高 B (mm)	Plunger Diam. 主軸直徑 J (mm)	Base Dimensions 底座尺寸 L x W (mm)	Auxiliary Height 輔助高 (mm)	Weight 總重 (kg)	Air pressure Rang 使用空壓 (kgf/cm^2)
STH-20A	20	150	235	385	50	128x238	16,45,80	14.5	8-12
STH-20B		125	210	335	50	128x238	16,45,80	13.5	8-12
STH-30A	30	145	240	385	60	141x257	16,45,80	19.6	8-12
STH-30B		120	215	335	60	141x257	16,45,80	18.6	8-12

STC 氣動式油壓千斤頂推車型

- 推車型設計使用輕便。
- 採用空氣動力泵浦、增加效率。
- 採用合金鋼主軸硬鉻處理，主軸均具自動回縮功能。
- 各型號均附墊塊組。

Air Hydraulic Truck Jack

※Trolley design for easy movement.
※Air pump increases efficiency.
※Chrome plated plunger with self-return.
※Saddle sets are included on all models.

STC-30L

STC-50

STC-50DL

STC-30

STC-50

STC-50DL

STC-50

Model Number 型 號	Cap. 能 力 (tons)	Stroke 揚 程 (mm)	Coll Height 本身高 A (mm)	Ext. Height 伸長總高 B (mm)	Plunger 主軸 C (mm)	Handle Height 柄高 D (mm)	Base Dimensions 底座尺寸 L x W (mm)	Auxiliary Height 輔助高度 (mm)	Air pressure Rang 使用空壓 (kgf/cm^2)	Weight 總 重 (kg)
STC-30L	30	120	224.5	350	60	1385	190x570	10,45,80	10-15	45.5
STC-50	50	130	242.5	375	65	1055	190x570	10,60,120	10-15	58.5
STC-50L	50	130	242.5	375	65	1390	190x570	10,60,120	10-15	58.5
STC-50L2	50	130	242.5	375	65	1690	190x570	10,60,120	10-15	58.5
STC-50L3	50	130	242.5	375	65	2190	190x570	10,60,120	10-15	58.5
STC-50DL	1st50 2nd30	140	160	300	ø85/ø55	1385	190x570	10,60,120	10-15	44.4